



motivated



GE energy smart® LED replacement lamps for
OFFICE spaces.



imagination at work

optimized

Welcome to a whole new outlook on Monday. The same way that a bold cup of coffee can kick off the perfect workday, GE energy smart® LED replacement lamps work hard to deliver the visual impact that inspires productivity. The bright white radiance of GE energy smart® LED replacement lamps isn't just something you see, it's something you feel.

For your office building or complex, we have an entire family of GE energy smart® LED replacement lamps that will enhance your environment and create a motivating, enjoyable, and impressive experience for your employees and clients.

financially smart

Emotional outcomes are just as real as the savings are tangible. You can expect to see significant energy savings, reduced operating expenses and increased revenue, beginning the moment you swap out inefficient lamps with GE energy smart® LED replacement lamps.







Throughout your office spaces, light is everywhere. But is it everything it can be in terms of quality and cost effectiveness? With GE energy smart® LED replacement lamps, we believe the answer is yes.

meeting areas

Coffee and bagels can help set a meeting in motion. But for a real kick-off with energy and vibrancy, consider GE energy smart® LED replacement lamps for your downlight and wall sconce fixtures.

replacement advantages

Saving Solution	Application #1 	Application #2 	Application #3 	Application #4 
Saving Comparison	Wall Sconce	Downlight	Downlight	Downlight
Existing lamp	Incandescent A19 60W (800 lumens)	Halogen PAR38 100W (1150 CBCP)	Halogen PAR30L 75W (1100 lumens)	Halogen MR16 50W (1500 CBCP)
GE energy smart® LED	GE energy smart® A19 13W (800 lumens)	GE energy smart® PAR38 20W (1250 lumens)	GE energy smart® PAR30L 12W (5100 CBCP) (750 lumens)	GE energy smart® MR16 7Wx (1500 CBCP)
Product number	65386	66327	65139	66525
Watts saved per lamp	47	80	63	43
Number of lamps	2	2	2	2
Total watts saved	94	160	126	86







Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

office space

Lighten up the work environment with GE energy smart® LED replacement lamps to inspire creativity and motivate productivity.

replacement advantages






Saving Solution	Application #1 	Application #2 	Application #3 	Application #4 
Saving Comparison	Wall Sconce	Downlight	Downlight	Downlight
Existing lamp	Incandescent A19 60W (800 lumens)	Halogen PAR38 100W (1150 CBCP)	Halogen PAR30L 75W (1100 lumens)	Halogen MR16 50W (1500 CBCP)
GE energy smart® LED	GE energy smart® A19 13W (800 lumens)	GE energy smart® PAR38 20W (1250 lumens)	GE energy smart® PAR30L 12W (5100 CBCP) (750 lumens)	GE energy smart® MR16 7Wx (2500 CBCP)
Product number	65386	66327	65139	66524
Watts saved per lamp	47	80	63	43
Number of lamps	2	2	2	2
Total watts saved	94	160	126	86



lobby and reception

Create a great first impression with a bright, cheery greeting from GE energy smart® LED replacement lamps for your table lamps, wall sconce and downlight fixtures.

replacement advantages






Saving Solution	Application #1 	Application #2 	Application #3 	Application #4 	Application #5 
Saving Comparison	Table Lamp/ Wall Sconce	Downlight	Downlight	Downlight	Downlight
Existing lamp	Incandescent A19 60W (800 lumens)	Halogen PAR38 100W (1150 CBCP)	Halogen MR16 50W (1500 CBCP)	Halogen PAR30L 75W (1100 lumens)	Halogen BR30 60W (650 lumens)
GE energy smart® LED	GE energy smart® A19 13W (800 lumens)	GE energy smart® PAR 38 20W (3700 CBCP) (1000 lumens)	GE energy smart® MR16 7Wx (2500 CBCP)	GE energy smart® PAR30L 12W (5100 CBCP) (750 lumens)	GE energy smart® BR30 12W (750 lumens)
Product number	65386	64289	66524	65139	65390
Watts saved per lamp	47	80	43	63	48
Number of lamps	2	2	2	2	2
Total watts saved	94	160	86	126	96



hallways and corridors

From point A to point B, help employees, clients and other visitors easily and securely find their way with GE energy smart® LED replacement lamps for your downlight and wall sconce fixtures.

replacement advantages

Saving Solution	Application #1 	Application #2 	Application #3 	Application #4 	Application #5 
Saving Comparison	Downlight	Downlight	Downlight	Downlight	Wall Sconce
Existing lamp	Halogen MR16 50W (1500 CBCP)	Halogen PAR30L 75W (1100 lumens)	Halogen PAR38 100W (1150 CBCP)	Halogen BR30 60W (650 lumens)	Incandescent A19 60W (800 lumens)
GE energy smart® LED	GE energy smart® MR16 7Wx (2500 CBCP)	GE energy smart® PAR30L 12W (5100 CBCP)	GE energy smart® PAR 38 20W (3700 CBCP) (1000 lumens)	GE energy smart® BR30 12W (750 lumens)	GE energy smart® A19 13W (800 lumens)
Product number	66524	65139	64289	65390	65386
Watts saved per lamp	43	63	80	48	47
Number of lamps	2	6	2	2	2
Total watts saved	86	378	160	96	94



Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

GE energy smart® LED replacement lamps

A-Line Lamps (Dimming)

BULB SHAPE	BASE TYPE	WATTS	ORDER CODE	DESCRIPTION	VOLTS	CASE QTY*	MOL (IN)	LUMENS INTIAL	CBCP	INITIAL COLOR TEMP	CRI	+RATED LIFE (YRS) 3HRS/DAY	*RATED LIFE L70(HRS)	ESTIMATED ENERGY COST/YR	ENERGY STAR® STATUS	ADDITIONAL INFORMATION
A-19																
	MED	9	66390	LED9DA19/827	120	6	4.43	450		2700	82	22.8	25,000	\$1.08	★	White, Omnidirectional
			65385	LED9DA19/830	120	6	4.43	450		3000	82	22.8	25,000	\$1.08	★	White, Omnidirectional
			64128	LED9DA19/830/TP	120	3	4.43	450		3000	82	22.8	25,000	\$1.08	★	White, Omnidirectional
	MED	13	65386	LED13DA19/830	120	6	4.43	800		3000	82	22.8	25,000	\$1.57	★	White, Omnidirectional
			64130	LED13DA19/830/TP	120	3	4.43	800		3000	82	22.8	25,000	\$1.57	★	White, Omnidirectional
	Locking Device		62182	LEDA19LOCKD EV		6										

A-Line Lamps (Non-Dimming)

BULB SHAPE	BASE TYPE	WATTS	ORDER CODE	DESCRIPTION	VOLTS	CASE QTY*	MOL (IN)	LUMENS INTIAL	CBCP	INITIAL COLOR TEMP	CRI	+RATED LIFE (YRS) 3HRS/DAY	*RATED LIFE L70(HRS)	ESTIMATED ENERGY COST/YR	ENERGY STAR® STATUS	ADDITIONAL INFORMATION
A-19																
	MED	9	62180	LED9A19/830/TP	120	3	4.43	450		3000	82	22.8	25,000	\$1.08	★	White, Omnidirectional
			64018	LED9A19/830	120	6	4.43	450		3000	82	22.8	25,000	\$1.08	★	White, Omnidirectional

Reflector Lamps (Dimming)

BULB SHAPE	BASE TYPE	WATTS	ORDER CODE	DESCRIPTION	VOLTS	CASE QTY*	MOL (IN)	LUMENS INTIAL	CBCP	INITIAL COLOR TEMP	CRI	+RATED LIFE (YRS) 3HRS/DAY	*RATED LIFE L70(HRS)	ESTIMATED ENERGY COST/YR	ENERGY STAR® STATUS	ADDITIONAL INFORMATION	
BR30																	
	BR30	MED	12	65389	LED12DBR30/827	120	6	5.37	750		2700	83	22.8	25,000	\$1.45	★	Frosted, Silver
				65388	LED12DBR30/827	120	3	5.37	750		2700	83	22.8	25,000	\$1.45	★	Frosted, Silver
				65390	LED12DBR30/830	120	6	5.37	750		3000	83	22.8	25,000	\$1.45	★	Frosted, Silver

Directional Lamps (Dimming)

BULB SHAPE	BASE TYPE	WATTS	ORDER CODE	DESCRIPTION	VOLTS	CASE QTY*	MOL (IN)	LUMENS INTIAL	CBCP	INITIAL COLOR TEMP	CRI	+RATED LIFE (YRS) 3HRS/DAY	*RATED LIFE L70(HRS)	ESTIMATED ENERGY COST/YR	ENERGY STAR® STATUS	ADDITIONAL INFORMATION	
12 Volt AC/DC MR16																	
Note: 35-watt Halogen replacements (based on ENERGY STAR® requirements for center beam candlepower)																	
	MR16	GU5.3	7	67843	LED7DMR16/840/15	12	6	1.88	430	4000	4000	80	22.8	25,000	\$0.84		Accent, 15° beam, Silver
				67844	LED7DMR16/840/25	12	6	1.88	430	2100	4000	80	22.8	25,000	\$0.84		Accent, 25° beam, Silver
				67845	LED7DMR16/840/35	12	6	1.88	430	1200	4000	80	22.8	25,000	\$0.84		Accent, 35° beam, Silver
				66127	LED7DMR16/830/15	12	6	1.88	390	3700	3000	80	22.8	25,000	\$0.84	★	Accent, 15° beam, Silver
				66128	LED7DMR16/830/25	12	6	1.88	390	1900	3000	80	22.8	25,000	\$0.84	★	Accent, 25° beam, Silver
				66126	LED7DMR16/NFL/TP	12	3	1.88	390	1900	3000	80	22.8	25,000	\$0.84	★	Accent, 25° beam, Silver
				66129	LED7DMR16/830/35	12	6	1.88	390	1100	3000	80	22.8	25,000	\$0.84	★	Accent, 35° beam, Silver
				66130	LED7DMR16/827/15	12	6	1.88	370	3700	2700	80	22.8	25,000	\$0.84	★	Accent, 15° beam, Silver
				66131	LED7DMR16/827/25	12	6	1.88	370	1900	2700	80	22.8	25,000	\$0.84	★	Accent, 25° beam, Silver
				66132	LED7DMR16/827/35	12	6	1.88	370	1100	2700	80	22.8	25,000	\$0.84	★	Accent, 35° beam, Silver
Note: 50-watt Halogen replacements (based on ENERGY STAR® requirements for center beam candlepower)																	
				66524	LED7XDMR16830/25	12	6	1.88	460	2500	3000	80	22.8	25,000	\$0.84	★	Accent, 25° beam, Silver
				66525	LED7XDMR16830/35	12	6	1.88	460	1500	3000	80	22.8	25,000	\$0.84	★	Accent, 35° beam, Silver
				66526	LED7XDMR16827/25	12	6	1.88	440	2400	1700	80	22.8	25,000	\$0.84	★	Accent, 25° beam, Silver
				66527	LED7XDMR16827/35	12	6	1.88	440	1400	2700	80	22.8	25,000	\$0.84	★	Accent, 35° beam, Silver
120 Volt GU10																	
	MR16	GU10	4.5	66137	LED4DGU10/NFL/TP	120	3	2.30	180		3000	80	22.8	25,000	\$0.48		Accent, 25° beam, Silver

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® qualified

^ Estimated energy cost per year based on \$0.11 per Kwh energy rate and 3 operating hours per day.

Notes: Product descriptions ending in */TP* indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hood display.

Get more information at
GELighting.com/ThinkLED

Directional Lamps (Dimming)

BULB SHAPE	BASE TYPE	WATTS	ORDER CODE	DESCRIPTION	VOLTS	CASE QTY*	MOL (IN)	LUMENS INTIAL	CBPC	INITIAL COLOR TEMP	CRI	+RATED LIFE (YRS) 3HRS/DAY	*RATED LIFE L70(HRS)	ESTIMATED ENERGY COST/YR	ENERGY STAR® STATUS	ADDITIONAL INFORMATION
Compact PAR30 (Concave Cover)																
PAR30	MED	12	65135	LED12DP30S830/20	120	6	3.75	750	5100	3000	84	22.8	25,000	\$1.45	★	Accent, 20° beam, Silver
			65136	LED12DP30S830/35	120	6	3.75	750	2050	3000	84	22.8	25,000	\$1.45	★	Accent, 35° beam, Silver
			65137	LED12DP30S827/30	120	6	3.75	740	5000	2700	83	22.8	25,000	\$1.45	★	Accent, 20° beam, Silver
			65138	LED12DP30S827/35	120	6	3.75	740	2000	2700	83	22.8	25,000	\$1.45	★	Accent, 35° beam, Silver
			65133	LED12DP30S/FL/TP	120	3	3.75	740	2000	2700	83	22.8	25,000	\$1.45	★	Accent, 35° beam, Silver
			65985	LED12DP30S827/25	120	6	3.75	740	3200	2700	83	22.8	25,000	\$1.45	★	Accent, 25° beam, Silver
			65986	LED12DP30W827/25	120	6	3.75	740	3200	2700	83	22.8	25,000	\$1.45	★	Accent, 25° beam, White
			65987	LED12DP30B827/25	120	6	3.75	740	3200	2700	83	22.8	25,000	\$1.45	★	Accent, 25° beam, Black
			67256	LED12DP30S840/20	120	6	3.75	840	5800	4000	85	22.8	25,000	\$1.45	★	Accent, 20° beam, Silver
			67257	LED12DP30S840/35	120	6	3.75	840	2600	4000	85	22.8	25,000	\$1.45	★	Accent, 35° beam, Silver
Compact PAR30 (Convex Cover)																
PAR30	MED	10	61922	LED10DP30S830/20	120	6	3.75	500	3720	3000	80	45.7	50,000	\$1.20	★	Accent, 20° beam, Silver
			61923	LED10DP30S827/20	120	6	3.75	450	3450	2700	80	45.7	50,000	\$1.20	★	Accent, 20° beam, Silver
			68013	LED10DP30S827/35	120	6	3.75	450	1240	2700	80	22.8	25,000	\$1.20	★	Accent, 35° beam, Silver
			64326	LED10DP30W827/20	120	6	3.75	450	3450	2700	80	45.7	50,000	\$1.20	★	Accent, 20° beam, White
			63026	LED10DP3/FL/TP	120	3	3.75	450	1240	2700	80	22.8	25,000	\$1.20	★	Accent, 35° beam, Silver
Compact PAR30 Long Neck (Concave Cover)																
PAR30	MED	12	65139	LED12DP3LS830/20	120	6	4.75	750	5100	3000	84	22.8	25,000	\$1.45	★	Accent, 20° beam, Silver
			65140	LED12DP3LS830/35	120	6	4.75	750	2050	3000	84	22.8	25,000	\$1.45	★	Accent, 35° beam, Silver
			65141	LED12DP3LS827/20	120	6	4.75	740	5000	2700	83	22.8	25,000	\$1.45	★	Accent, 20° beam, Silver
			65142	LED12DP3LS827/35	120	6	4.75	740	2000	2700	83	22.8	25,000	\$1.45	★	Accent, 35° beam, Silver
			65134	LED12DP3LS/FL/TP	120	3	4.75	740	2000	2700	83	22.8	25,000	\$1.45	★	Accent, 35° beam, Silver
Compact PAR30 Long Neck (Convex Cover)																
PAR30L	MED	10	61924	LED10DP3LS830/20	120	6	4.75	500	3720	3000	80	22.8	50,000	\$1.20	★	Accent, 20° beam, Silver
			61925	LED10DP3LS827/20	120	6	4.75	450	3450	2700	80	22.8	50,000	\$1.20	★	Accent, 20° beam, Silver
			68014	LED10DP3LS827/35	120	6	4.75	450	1240	2700	80	22.8	25,000	\$1.20	★	Accent, 35° beam, Silver
			63027	LED10DP3L/FL/TP	120	3	4.75	450	1240	2700	80	22.8	25,000	\$1.20	★	Accent, 35° beam, Silver
Commercial PAR38 (Indoor/Outdoor)																
PAR38	MED	12	66111	LED12DP38S830/12	120	6	5.31	700	10000	3000	82	22.8	25,000	\$1.45	★	Spot, 12° beam, Silver
			66112	LED12DP38S830/25	120	6	5.31	700	3300	3000	82	22.8	25,000	\$1.45	★	Narrow Flood, 25° beam, Silver
			66113	LED12DP38S830/35	120	6	5.31	700	1500	3000	82	22.8	25,000	\$1.45	★	Flood, 35° beam, Silver
			66529	LED12DP38/FL/TP	120	3	5.31	700	1500	3000	82	22.8	25,000	\$1.45	★	Flood, 35° beam, Silver
			66114	LED12DP38S827/12	120	6	5.31	660	10000	2700	82	22.8	25,000	\$1.45	★	Spot, 12° beam, Silver
			66115	LED12DP38S827/25	120	6	5.31	660	3300	2700	82	22.8	25,000	\$1.45	★	Narrow Flood, 25° beam, Silver
			66116	LED12DP38S827/35	120	6	5.31	660	1500	2700	82	22.8	25,000	\$1.45	★	Flood, 35° beam, Silver
		20	64827	LED20DP38S830/15	120	6	5.31	1100	9000	3000	80	45.7	50,000	\$2.41	★	Spot, 15° beam, Silver
			64391	LED20DP38S830/25	120	6	5.31	1100	4000	3000	80	45.7	50,000	\$2.41	★	Narrow Flood, 25° beam, Silver
			64392	LED20DP38S830/40	120	6	5.31	1100	1800	3000	80	45.7	50,000	\$2.41	★	Flood, 40° beam, Silver
			64828	LED20DP38S827/15	120	6	5.31	1000	8500	2700	80	45.7	50,000	\$2.41	★	Spot, 15° beam, Silver
			64829	LED20DP38S827/25	120	6	5.31	1000	3700	2700	80	45.7	50,000	\$2.41	★	Narrow Flood, 25° beam, Silver
			64830	LED20DP38S827/40	120	6	5.31	1000	1700	2700	80	45.7	50,000	\$2.41	★	Flood, 40° beam, Silver
			65847	LED20DP38/FL/TP	120	3	5.31	1000	1700	2700	80	22.8	25,000	\$2.41	★	Flood, 40° beam, Silver
			66326	LED20DP38S840/15	120	6	5.31	1250	10000	4000	80	22.8	25,000	\$2.41	★	Spot, 15° beam, Silver
			66327	LED20DP38S840/25	120	6	5.31	1250	5500	4000	80	22.8	25,000	\$2.41	★	Narrow Flood, 25° beam, Silver
			66328	LED20DP38S840/40	120	6	5.31	1250	2300	4000	80	22.8	25,000	\$2.41	★	Flood, 40° beam, Silver

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® qualified

^ Estimated energy cost per year based on \$0.11 per Kwh energy rate and 3 operating hours per day.

Notes: Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hood display.

Get more information at
GELighting.com/ThinkLED

Directional Lamps (Non-Dimming)

BULB SHAPE	BASE TYPE	WATTS	ORDER CODE	DESCRIPTION	VOLTS	CASE QTY*	MOL (IN)	LUMENS INTIAL	CBCP	INITIAL COLOR TEMP	CRI	+RATED LIFE (YRS) 3HRS/DAY	*RATED LIFE L70(HRS)	ESTIMATED ENERGY COST/YR	ENERGY STAR® STATUS	ADDITIONAL INFORMATION
12 Volt AC/DC MR16																
MR16	GU5.3	4	62915	LED4MR16/NFL/TP	12	3	1.88	210	800	3000	80	22.8	25,000	\$0.48		Accent, 25° beam, Silver
			62916	LED4MR16/830/15	12	24**	1.88	210	1350	3000	80	22.8	25,000	\$0.48		Accent, 15° beam, Silver
			62917	LED4MR16/830/25	12	24**	1.88	210	800	3000	80	22.8	25,000	\$0.48		Accent, 25° beam, Silver
			67214	LED4MR16/830/35	12	6	1.88	240	580	3000	84	22.8	25,000	\$0.48	★	Accent, 35° beam, Silver
			63747	LED4MR16/827/15	12	24**	1.88	200	1250	2700	80	22.8	25,000	\$0.48		Accent, 15° beam, Silver
			63748	LED4MR16/827/25	12	24**	1.88	200	750	2700	80	22.8	25,000	\$0.48		Accent, 25° beam, Silver
			63749	LED4MR16/827/36	12	24**	1.88	200	400	2700	80	22.8	25,000	\$0.48		Accent, 35° beam, Silver
120 Volt GU10																
MR16	GU10	1	73153	LED1GU10/NFL20/CD	120	3	2.30	35	100	5500	70		12,000	\$0.12		Deco Light, 20° beam, Silver
		4	75625	LED4GU10/NFL/CD	120	3	2.30	100	250	3050	82	13.7	15,000	\$0.48		Accent, 25° beam, Silver
			75865	LED4GU10/NFL/TP	120	3	2.30	100	250	3050	82	13.7	15,000	\$0.48		Accent, 25° beam, Silver
		4.5	62909	LED5GU10/NFL/TP	120	3	2.30	200	800	3000	82	22.8	25,000	\$0.54	★	Accent, 25° beam, Silver
			64887	LED5GU10S830/25	120	6	2.30	200	800	3000	82	22.8	25,000	\$0.54	★	Accent, 25° beam, Silver
Compact PAR30 (Convex Cover)																
PAR30	MED	10	75376	LED10P30/NFL/TP	120	3	3.75	340	1400	3000	82	27.4	30,000	\$1.20		Accent, 24° beam, Silver
			75613	LED10P30S830/24	120	6	3.75	340	1400	3000	82	27.4	30,000	\$1.20		Accent, 24° beam, Silver
			76144	LED10P30S827/24	120	6	3.75	340	1300	2700	82	27.4	30,000	\$1.20		Accent, 24° beam, Silver
Compact PAR30 Long Neck (Convex Cover)																
PAR30L	MED	10	75377	LED10P3L/NFL/TP	120	3	4.75	340	1400	3000	82	27.4	30,000	\$1.20		Accent, 24° beam, Silver
			76145	LED10P3LS827/24	120	6	4.75	320	1300	2700	82	27.4	30,000	\$1.20		Accent, 24° beam, Silver
Commercial PAR38 (Indoor/Outdoor)																
PAR38	MED	20	61927	LED20P38S/FL	120	3	5.31	1050	1300	3000	80	22.8	25,000	\$2.41	★	Flood, 40° beam, Silver
			61928	LED20P38S830/40	120	6	5.31	1050	1300	3000	80	45.7	50,000	\$2.41	★	Flood, 40° beam, Silver
			61929	LED20P38S830/25	120	6	5.31	1050	4000	3000	80	45.7	50,000	\$2.41	★	Narrow Flood, 25° beam, Silver

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions

Get more information at
GELighting.com/ThinkLED

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® qualified

^ Estimated energy cost per year based on \$0.11 per Kwh energy rate and 3 operating hours per day.

Notes: Product descriptions ending in */TP* indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hood display.

Motivate employees and clients like never before — the moment you turn on a GE energy smart® LED replacement lamp.

Light influences people's emotions, how they view their space and their world, and how they start and end their day. GE understands this and wants to help transform your stores, buildings or facilities, while ensuring your upfront investment is paid back as quickly as possible.

If you're inspired to enhance your space—with substantial savings—call your GE Lighting representative.

To experience what we've done for our existing customers, see case studies, or to request a free lighting audit, visit gelighting.com/ThinkLED

ecomaginationSM



imagination at work



energy smart® is a registered trademark of GE
ENERGY STAR® and the ENERGY STAR® logo are registered U.S. marks
© 2012 GE 69199 8/2012 Printed in USA