

FAS1075
Power Patrol
 By **INTERSTATE BATTERIES**

FIRE & SECURITY



RA.V1

Technical Specifications

Nominal Voltage	12V
Nominal Capacity	7.0Ah (20 Hr Rate to 1.75V/cell)
Chemistry	Lead Acid - AGM

Physical Specifications

Length	151mm	5.94in
Width	65mm	2.56in
Height	94mm	3.70in
Height w/Terminal	100mm	3.93in
Weight (+/- 5%)	2.00Kg	4.41lbs
Terminal Type	.187" Faston Tabs	
Case Material	Black ABS	

Charging Specifications

Charge Voltage	Battery	Per Cell
Float	13.7V~13.9V	2.28V~2.31V
Cycle	14.6V~14.8V	2.43V~2.46V
Max. Charge Current	2.1A	
Charge Temperature Range	32°F (0°C) 122°F (50°C)	

Capacity Specifications

5 Second Discharge Current	70A
Self Discharge (to 80% capacity)	1 Month 97%
	3 Months 91%
	6 Months 83%
Internal Resistance	30 mΩ(25°C)
Discharge Temperature Range	-4°F (-20°C) to 140°F (60°C)

FEATURES:

- Professional-grade quality developed specifically for fire & security applications
- Designed for optimum efficiency and long life in float charge devices
- Industry-leading AGM design
- VRLA technology to eliminate spills and over-pressurization
- Flexibility of mounting orientation
- Maintenance-free

