

Whelen's PAR-46 Series is engineered to provide brilliant light output for thousands of operating hours in a lightweight and low current design.

REPLACEMENT LAMPS

- Drop-in replacements for outdated halogen lamps
- Patent Pending: (P46SLC, P46S2*, P46S2*3) Internal thermal regulator maximizes the lifespan of the LED diodes. Internal circuitry and unique optics provide an intense and even circular lighting pattern
- Go undercover with all new, SAE Class 1 certified smoked lenses
- 4" (102mm) Round



P46S2R3



P46S2X



P46FLB



P46FLR



P46S2X



P46WLC



P46FLB



P46FLR



P46FLC



P46SLC



P46FLCX

MODELS

Model	Lamp	Usage	Diodes	Color	Lumens	VDC	Amps	Weight	Lens	Control
P46SC	2°	Spotlight replacement	9	White	2000	12	2.3	1lb.	Clear	
P46SCX	Spotlight			White					Smoked	
P46FLCX	8°			White					Smoked	
P46FL*	Spotlight	Floodlight replacement	18	Amber, Blue, Red, or White	1600	12	1.9	1lb.	Clear	
P46WL*	20° x 60°			White					Clear	
P46WLCX	Floodlight			White					Smoked	
P46S2*	DUO™ 8° spotlight	Replacement for Unity® spotlight mounting only	18	White spot, Red or Blue warning	1200	12	1.4	1lb.	Clear	One wire control for spot and warning
P46S2*3	8°									One wire color control for spot, warning, and alternate flash of spot/warning
P46S2X	8°			White spot, California Steady Red						One wire control of spotlight override
P46S2X2	Spotlight									One wire control of steady Red override

Replace * in model number with warning color desired: ● ● ● ○
A=Amber, B=Blue, R=Red, C=Clear/White

WARNING: These products may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit whelen.com/regulatory.

WORK LIGHTS

- Available in spotlight, floodlight, or combination spotlight/warning models
- Hard-coated lenses minimize environmental damage from sand, sun, salt, and road chemicals
- Low current draw
- Reverse polarity protected
- Rated to last thousands of hours
- Black powder coated die-cast aluminum heatsink
- Ventilation system reduces moisture build-up
- Models emit zero EMC radiation
- SAE J1113-42 Class 5 EMC Certified
- Five year warranty

HANDHELD SPOTLIGHT

- Includes 90lb. pull magnet mount, 8' coiled cord, and cigar plug
- Durable push-button On/Off switch

RUBBER SWIVEL SPOTLIGHT/FLOODLIGHT

- Available in DUO™ models with an 8° spotlight and Blue or Red warning, with independent control of spotlight and warning functions, and spotlight override
- Includes stainless steel bracket and hardware



MODELS

Model	Lamp	Mount	Diodes	Color	Lumens	VDC	Amps	Control	Dimensions
P46SLCHG	2° Spotlight	Rubber swivel	9	White	1800	12	2.3	-	7-3/8" (188mm) H x 3-3/4" (94mm) D x 6" (152mm) Dia.
P46S3*H	DUO 8° Spotlight		18	White, Red, Blue	1200		1.4		
P46HHS	2° Spotlight	Handheld	9	White	1800		2.5	Built-in On/Off switch	10-1/2" (270mm) H x 3-3/4" (94mm) D x 6" (152mm) Dia.

Replace * in model number with warning color desired: R=Red, B=Blue, W=White ● ● ○

WARNING: These products may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit whelen.com/regulatory.

WHELEN

51 Winthrop Road
Chester, Connecticut 06412-0684
(860) 526-9504 www.whelen.com

Whelen Engineering reserves the right to upgrade and improve products without notice.
© 2019 Whelen Engineering Company, Inc. Printed in U.S.A.
NASCAR® is a registered trademark of the National Association for Stock Car Auto Racing, Inc.
Code No. 122581 - 09/13/19

WHELEN
OFFICIAL WARNING LIGHTS



All products proudly designed, manufactured, and assembled in the U.S.A.
• ISO 9001 Registered QMS