

GE  
Lighting

# awaken



LED replacement lamps



ecomagination™



imagination at work

# exceeding expectations

## Why choose GE'S LED Lamps?

### Innovation leadership

A GE scientist invented the first visible LED in 1962, pioneering a technology that is revolutionizing the lighting industry. That was our start and now we are dedicated to constantly improving LED performance. We continually invest in new products and the latest upgrades to make sure our best LED solutions are available.

### Trust

We've been here. We'll be here. Built into each of GE's LED replacement lamps is 125 years of experience, reliability and innovation. Every performance claim we make is supported by stringent, comprehensive testing—ensuring that your lighting investment pays off today and in the future.

### Long life

GE's LED replacement lamps are sturdy, dependable and long lasting. Depending on the lamp, you can expect up to 50,000 hours of rated life. That's 12 hours a day, every day of the year, for over a decade.

### Short payback period

Decreased energy and maintenance costs, combined with utility rebates, deliver results that often exceed your expectations.

### Family of solutions

Directional. Omni-directional. Decorative. Dimming. Tight optical control. Accent. Task. Display. Indoor. Outdoor. You name it. We've got it in LED.



LED replacement lamps

Decorative Lamps

| Bulb Shape                                                                       | Base Type | Watts | Order Code | Description     | Volts           | Case Qty**      | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI  | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information |
|----------------------------------------------------------------------------------|-----------|-------|------------|-----------------|-----------------|-----------------|----------|----------------|------|--------------------|------|---------------------|-----------------------|----------|---------------------|------------------|------------------------|
| Candles                                                                          |           |       |            |                 |                 |                 |          |                |      |                    |      |                     |                       |          |                     |                  |                        |
|  | CA11      | MED   | 3.5        | 68168           | LED3DCAM-C/TP   | 120             | 3        | 4.2            | 170  | 2700               | 80   | 25W                 | 15,000                | Yes      |                     | Damp             | Clear, Bent tip        |
|                                                                                  |           |       |            | 68167           | LED4DCAM-F/TP   | 120             | 3        | 4.2            | 270  | 2700               | 82   | 25W                 | 15,000                | Yes      |                     | Damp             | Frost, Bent tip        |
|                                                                                  |           |       |            | 21250           | LED4DCAM-C3/827 | 120             | 6        | 4.2            | 300  | 2700               | 80   | 40W                 | 15,000                | Yes      | ★                   | Damp             | Clear, Bent tip        |
|                                                                                  |           |       |            | 69111           | LED4DCAM-C3/850 | 120             | 6        | 4.2            | 300  | 5000               | 80   | 40W                 | 15,000                | Yes      | ★                   | Damp             | Clear, Bent tip        |
|                                                                                  |           |       |            | 75554           | LED4DCAMCF/824  | 120             | 6        | 4.2            | 250  | 2400               | 80   | 25W                 | 15,000                | Yes      |                     | Damp             | Clear, Bent tip        |
|  | CAND      | 3.5   | 21251      | LED7DCAM-C3/827 | 120             | 6               | 4.8      | 500            | 2700 | 80                 | 60W  | 15,000              | Yes                   | ★        | Damp                | Clear, Bent tip  |                        |
|                                                                                  |           |       | 68166      | LED3DCAC-C/TP   | 120             | 3               | 4.3      | 170            | 2700 | 80                 | 25W  | 15,000              | Yes                   |          | Damp                | Clear, Bent tip  |                        |
|                                                                                  |           |       | 4          | 68165           | LED4DCAC-F/TP   | 120             | 3        | 4.3            | 270  | 2700               | 82   | 25W                 | 15,000                | Yes      |                     | Damp             | Frost, Bent tip        |
|                                                                                  |           |       | 21231      | LED4DCAC-C3/827 | 120             | 6               | 4.3      | 300            | 2700 | 80                 | 40W  | 15,000              | Yes                   | ★        | Damp                | Clear, Bent tip  |                        |
|                                                                                  |           |       | 69109      | LED4DCAC-C3/850 | 120             | 6               | 4.3      | 300            | 5000 | 80                 | 40W  | 15,000              | Yes                   | ★        | Damp                | Clear, Bent tip  |                        |
|                                                                                  |           |       | 75553      | LED4DCACCF/824  | 120             | 6               | 4.3      | 250            | 2400 | 80                 | 25W  | 15,000              | Yes                   |          | Damp                | Clear, Bent tip  |                        |
|                                                                                  |           |       | 7          | 21233           | LED7DCAC-C3/827 | 120             | 6        | 4.8            | 500  | 2700               | 80   | 60W                 | 15,000                | Yes      | ★                   | Damp             | Clear, Bent tip        |
| Globes                                                                           |           |       |            |                 |                 |                 |          |                |      |                    |      |                     |                       |          |                     |                  |                        |
|  | G16.5     | CAND  | 4.5        | 68169           | LED4DG16C-W/TP  | 120             | 3        | 3.0            | 270  | 2700               | 82   | 25W                 | 15,000                | Yes      |                     | Damp             | White                  |
|                                                                                  |           |       |            | 68170           | LED4DG16C-C/TP  | 120             | 3        | 3.0            | 270  | 2700               | 82   | 25W                 | 15,000                | Yes      |                     | Damp             | Clear                  |
|  | G25       | MED   | 4.5        | 68171           | LED4DG25M-W/TP  | 120             | 3        | 4.3            | 280  | 2700               | 82   | 25W                 | 15,000                | Yes      |                     | Damp             | White                  |
|                                                                                  |           |       |            | 68172           | LED4DG25M-C/TP  | 120             | 3        | 4.3            | 280  | 2700               | 82   | 25W                 | 15,000                | Yes      |                     | Damp             | Clear                  |
|                                                                                  |           |       |            | 21253           | LED5DG25-W3/827 | 120             | 6        | 4.3            | 350  | 2700               | 80   | 40W                 | 15,000                | Yes      | ★                   | Damp             | White                  |
|                                                                                  |           |       |            | 7               | 21255           | LED7DG25-W3/827 | 120      | 6              | 4.3  | 500                | 2700 | 80                  | 60W                   | 15,000   | Yes                 | ★                | Damp                   |
|                                                                                  |           |       |            |                 |                 |                 |          |                |      |                    |      |                     |                       |          |                     |                  |                        |

Filament Lamps

| Bulb Shape                                                                         | Base Type | Watts  | Order Code | Description | Volts            | Case Qty** | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information       |
|------------------------------------------------------------------------------------|-----------|--------|------------|-------------|------------------|------------|----------|----------------|------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|------------------------------|
| Candles                                                                            |           |        |            |             |                  |            |          |                |      |                    |     |                     |                       |          |                     |                  |                              |
|  | ST19      | MED    | 5          | 33025       | LED5DST19-V-OT2P | 120        | 8        | 5              | 440  | 2500               |     | 40W                 | 15,000                | Yes      |                     | Damp             | 4, 2-packs, Vintage Filament |
|                                                                                    |           |        | 3          | 76018       | LED3DST19-V      | 120        | 6        | 5              | 440  | 2500               |     | 25W                 | 15,000                | Yes      |                     | Damp             | Vintage Filament             |
|  | CA11      | Candle | 3          | 75915       | LED3DCAC-V       | 120        | 6        | 4.4            | 300  | 2500               | 80  | 40W                 | 15,000                | Yes      |                     | Damp             | Bent Tip, Vintage Filament   |
|                                                                                    |           | MED    | 3          | 75914       | LED3DCAM-V       | 120        | 6        | 4.4            | 300  | 2500               | 80  | 40W                 | 15,000                | Yes      |                     | Damp             | Bent Tip, Vintage Filament   |

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

\*\* Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

# UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at  
GELighting.com/ThinkLED

# LED replacement lamps

## A-Line Lamps

| Bulb Shape                                                                       | Base Type | Watts | Order Code | Description      | Volts            | Case Qty**    | MOL (In) | Lumens Initial | CBCP          | Initial Color Temp | CRI  | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information |                        |
|----------------------------------------------------------------------------------|-----------|-------|------------|------------------|------------------|---------------|----------|----------------|---------------|--------------------|------|---------------------|-----------------------|----------|---------------------|------------------|------------------------|------------------------|
| A-15                                                                             |           |       |            |                  |                  |               |          |                |               |                    |      |                     |                       |          |                     |                  |                        |                        |
|  | MED       | 4     | 34038      | LED4DA15-W3/827  | 120              | 6             | 3.5      | 300            |               | 2700               | 80   | 40W                 | 15,000                | Yes      |                     | Damp             | White                  |                        |
|                                                                                  |           |       | 34051      | LED4DA15-C3/827  | 120              | 6             | 3.5      | 300            |               | 2700               | 80   | 40W                 | 15,000                | Yes      |                     | Damp             | Clear                  |                        |
| A-19                                                                             |           |       |            |                  |                  |               |          |                |               |                    |      |                     |                       |          |                     |                  |                        |                        |
|  | MED       | 6     | 69115      | LED6DA19/827     | 120              | 6             | 4.4      | 480            |               | 2700               | 80   | 40W                 | 15,000                | Yes      | ★                   | Damp             | White, Omnidirectional |                        |
|                                                                                  |           |       | 69118      | LED6DA19/830     | 120              | 6             | 4.4      | 480            |               | 3000               | 80   | 40W                 | 15,000                | Yes      | ★                   | Damp             | White, Omnidirectional |                        |
|                                                                                  |           |       | 69132      | LED6DA19/840     | 120              | 6             | 4.4      | 480            |               | 4000               | 80   | 40W                 | 15,000                | Yes      | ★                   | Damp             | White, Omnidirectional |                        |
|                                                                                  |           |       | 69144      | LED6DA19/850     | 120              | 6             | 4.4      | 480            |               | 5000               | 80   | 40W                 | 15,000                | Yes      | ★                   | Damp             | White, Omnidirectional |                        |
|  | MED       | 7     | 14063      | LED7DAV3/827W    | 120              | 6             | 4.6      | 470            |               | 2700               | 80   | 40W                 | 25,000                | Yes      |                     | Damp             | White, Semi-Omni       |                        |
|                                                                                  |           |       | 95928      | LED7DAV3/5K      | 120              | 6             | 4.6      | 500            |               | 5000               | 80   | 40W                 | 25,000                | Yes      |                     | Damp             | White, Semi-Omni       |                        |
|                                                                                  |           |       | 34238      | LED7DA19/824     | 120              | 6             | 4.44     | 450            |               | 2400               | 80   | 40W                 | 25000                 | Yes      |                     | Damp             | White                  |                        |
|                                                                                  |           | 10    | 69117      | LED10DA19/827    | 120              | 6             | 4.4      | 800            |               | 2700               | 80   | 60W                 | 15,000                | Yes      | ★                   | Damp             | White, Omnidirectional |                        |
|                                                                                  |           |       | 69119      | LED10DA19/830    | 120              | 6             | 4.4      | 800            |               | 3000               | 80   | 60W                 | 15,000                | Yes      | ★                   | Damp             | White, Omnidirectional |                        |
|                                                                                  |           |       | 69133      | LED10DA19/840    | 120              | 6             | 4.4      | 800            |               | 4000               | 80   | 60W                 | 15,000                | Yes      | ★                   | Damp             | White, Omnidirectional |                        |
|                                                                                  |           |       | 69146      | LED10DA19/850    | 120              | 6             | 4.4      | 800            |               | 5000               | 80   | 60W                 | 15,000                | Yes      | ★                   | Damp             | White, Omnidirectional |                        |
|                                                                                  |           | 10.5  | 95927      | LED11DAV3/5K     | 120              | 6             | 4.4      | 850            |               | 5000               | 80   | 60W                 | 15,000                | Yes      |                     | Damp             | White, Semi-Omni       |                        |
|                                                                                  |           |       | GU24       | 11               | 29268            | LED11DA19/824 | 120      | 6              | 4.44          | 800                |      | 2400                | 80                    | 60W      | 25,000              | Yes              |                        | Damp                   |
|                                                                                  |           |       |            | 74357            | LED11DA19827GU24 | 120           | 6        | 4.4            | 800           |                    | 2700 | 80                  | 60W                   | 25,000   | Yes                 |                  | Damp                   | White, Omnidirectional |
| A-21                                                                             |           |       |            |                  |                  |               |          |                |               |                    |      |                     |                       |          |                     |                  |                        |                        |
|  | MED       | 12    | 76037      | LED12DA19/827    | 120              | 6             | 5.16     | 1100           |               | 2700               | 80   | 75W                 | 15,000                |          |                     | Damp             | White, Omni, ES 2.0    |                        |
|                                                                                  |           |       | 76041      | LED12DA21/830    | 120              | 6             | 5.16     | 1100           |               | 3000               | 80   | 75W                 | 15,000                |          |                     | Damp             | White, Omni, ES 2.0    |                        |
|                                                                                  |           |       | 76045      | LED12DA21/840    | 120              | 6             | 5.16     | 1100           |               | 4000               | 80   | 75W                 | 15,000                |          |                     | Damp             | White, Omni, ES 2.0    |                        |
|                                                                                  |           |       | 76102      | LED12DA21/850    | 120              | 6             | 5.16     | 1100           |               | 5000               | 80   | 75W                 | 15,000                |          |                     | Damp             | White, Omni, ES 2.0    |                        |
|  | MED       | 12    | 73404      | LED12DA21/850FE  | 120              | 6             | 5.31     | 1100           |               | 5000               | 80   | 75W                 | 25,000                | Yes      |                     | Enclosed         | White, Enclosed, Omni  |                        |
|                                                                                  |           |       | 73384      | LED12DA21/830FE  | 120              | 6             | 5.31     | 1100           |               | 3000               | 80   | 75W                 | 25,000                | Yes      |                     | Enclosed         | White, Enclosed, Omni  |                        |
|                                                                                  |           | 13    | 12422      | LED13DA212/827   | 120              | 6             | 5.28     | 1100           |               | 2700               | 80   | 75W                 | 25,000                | Yes      |                     | Damp             | White, Omnidirectional |                        |
|                                                                                  |           |       | 14         | 94936            | LED14DA21/827W   | 120           | 6        | 5.28           | 1100          |                    | 2700 | 80                  | 75W                   | 15,000   | Yes                 |                  | Damp                   | White, Semi-Omni       |
|                                                                                  |           | 15    | 76038      | LED15DA21/827    | 120              | 6             | 5.16     | 1600           |               | 2700               | 80   | 100W                | 15,000                |          |                     | Damp             | White, Omni, ES 2.0    |                        |
|                                                                                  |           |       | 76043      | LED15DA21/830    | 120              | 6             | 5.16     | 1600           |               | 3000               | 80   | 100W                | 15,000                |          |                     | Damp             | White, Omni, ES 2.0    |                        |
|                                                                                  |           |       | 76060      | LED15DA21/840    | 120              | 6             | 5.16     | 1600           |               | 4000               | 80   | 100W                | 15,000                |          |                     | Damp             | White, Omni, ES 2.0    |                        |
|                                                                                  |           |       | 76117      | LED15DA21/850    | 120              | 6             | 5.16     | 1600           |               | 5000               | 80   | 100W                | 15,000                |          |                     | Damp             | White, Omni, ES 2.0    |                        |
|                                                                                  |           | 16    | 12349      | LED16DA212/827   | 120              | 6             | 5.28     | 1600           |               | 2700               | 80   | 100W                | 25,000                | Yes      |                     | Damp             | White, Omnidirectional |                        |
|                                                                                  |           |       | 12399      | LED16DA212/830   | 120              | 6             | 5.28     | 1600           |               | 3000               | 80   | 100W                | 25,000                | Yes      |                     | Damp             | White, Omnidirectional |                        |
|                                                                                  |           | GU24  |            | 92498            | LED16DA21827GU24 | 120           | 6        | 5.43           | 1600          |                    | 2700 | 80                  | 100W                  | 25,000   | Yes                 |                  | Damp                   | White, Omnidirectional |
|                                                                                  |           | MED   | 16         | 73376            | LED16A30/100/827 | 120           | 6        | 5.31           | 360/1400/900  |                    | 2700 | 80                  | 30/70/100             | 25,000   | -                   | ★                | Damp                   | White, 3-Way           |
| 92118                                                                            |           |       |            | LED16A30/100/5KB | 120              | 3             | 5.31     | 360/1400/900   |               | 5000               | 80   | 30/70/100           | 25,000                | -        | ★                   |                  | White, 3-Way           |                        |
|                                                                                  |           | 17    | 16113      | LED17DA21/827    | 120              | 6             | 5.28     | 1600           |               | 2700               | 78   | 100W                | 15,000                | Yes      |                     | Damp             | White, Semi-Omni       |                        |
|                                                                                  |           |       | 22         | 73378            | LED22A50/150/827 | 120           | 6        | 5.31           | 700/2155/1600 |                    | 2700 | 80                  | 50/100/150            | 25,000   | -                   |                  | Damp                   | White, 3-Way           |
|                                                                                  |           |       |            | 92120            | LED22A50/150/5KB | 120           | 3        | 5.31           | 700/2155/1600 |                    | 5000 | 80                  | 50/100/150            | 25,000   | -                   |                  |                        | White, 3-Way           |

## LED Bright Stik™

| Bulb Shape                                                                         | Base Type | Watts | Order Code | Description   | Volts | Case Qty** | MOL (in) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information |
|------------------------------------------------------------------------------------|-----------|-------|------------|---------------|-------|------------|----------|----------------|------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|------------------------|
| LED Bright Stik™                                                                   |           |       |            |               |       |            |          |                |      |                    |     |                     |                       |          |                     |                  |                        |
|  | Med       | 5.5   | 66256      | LED5.5LS3/827 | 120   | 48         | 4.45     | 450            |      | 2700               | 80  | 40W                 | 15,000                | -        | ★                   | Damp             | Case = 16 3-pack       |
|                                                                                    |           |       | 75177      | LED5.5LS3/850 | 120   | 48         | 4.45     | 450            |      | 5000               | 80  | 40W                 | 15,000                | -        | ★                   | Damp             | Case = 16 3-pack       |
|                                                                                    | Med       | 6     | 35517      | LED6LS3/828   | 120   | 48         | 4.45     | 450            |      | 2850               | 80  | 40W                 | 15,000                | -        |                     | Indoor           | Case = 16 3-pack       |
|                                                                                    |           |       | 35519      | LED6LS3/850   | 120   | 48         | 4.45     | 450            |      | 5000               | 80  | 40W                 | 15,000                | -        |                     | Indoor           | Case = 16 3-pack       |
|                                                                                    | Med       | 9     | 75184      | LED9LS3/827   | 120   | 48         | 4.45     | 800            |      | 2700               | 80  | 60W                 | 15,000                | -        | ★                   | Damp             | Case = 16 3-pack       |
|                                                                                    |           |       | 75588      | LED9LS3/850   | 120   | 48         | 4.45     | 800            |      | 5000               | 80  | 60W                 | 15,000                | -        | ★                   | Damp             | Case = 16 3-pack       |
|                                                                                    | Med       | 10    | 32273      | LED10LS3/850  | 120   | 48         | 4.45     | 760            |      | 5000               | 80  | 60W                 | 15,000                | -        |                     | Indoor           | Case = 16 3-pack       |
|                                                                                    |           |       | 75590      | LED12LS2/827  | 120   | 32         | 5.24     | 1100           |      | 2700               | 80  | 75W                 | 15,000                | -        | ★                   | Damp             | Case = 16 2-pack       |
|                                                                                    | Med       | 12    | 75591      | LED12LS2/850  | 120   | 32         | 5.24     | 1100           |      | 5000               | 80  | 75W                 | 15,000                | -        | ★                   | Damp             | Case = 16 2-pack       |
|                                                                                    |           |       | 35520      | LED14LS2/828  | 120   | 32         | 5.24     | 1060           |      | 2850               | 80  | 75W                 | 15,000                | -        |                     | Indoor           | Case = 16 2-pack       |
|                                                                                    | Med       | 14    | 35522      | LED14LS2/850  | 120   | 32         | 5.24     | 1060           |      | 5000               | 80  | 75W                 | 15,000                | -        |                     | Indoor           | Case = 16 2-pack       |
|                                                                                    |           |       | 35523      | LED16LS2/828  | 120   | 32         | 5.24     | 1520           |      | 2850               | 80  | 100W                | 15,000                | -        |                     | Indoor           | Case = 16 2-pack       |
|  | Med       | 16    | 35524      | LED16LS2/850  | 120   | 32         | 5.24     | 1520           |      | 5000               | 80  | 100W                | 15,000                | -        |                     | Indoor           | Case = 16 2-pack       |

### Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

\*\* Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

# UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at  
[GELighting.com/ThinkLED](http://GELighting.com/ThinkLED)

LED replacement lamps

Reflector Lamps

| Bulb Shape                                                                       | Base Type | Watts | Order Code | Description     | Volts | Case Qty" | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information |
|----------------------------------------------------------------------------------|-----------|-------|------------|-----------------|-------|-----------|----------|----------------|------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|------------------------|
| R20                                                                              |           |       |            |                 |       |           |          |                |      |                    |     |                     |                       |          |                     |                  |                        |
|  | MED       | 7     | 38268      | LED7DR20/827    | 120   | 6         | 3.64     | 470            |      | 2700               | 80  |                     | 25,000                | Yes      |                     | Damp             | White                  |
|                                                                                  |           |       | 43233      | LED7DR20/830    | 120   | 6         | 3.64     | 470            |      | 3000               | 80  |                     | 25,000                | Yes      |                     | Damp             | White                  |
|                                                                                  |           |       | 38273      | LED7DR20/850    | 120   | 6         | 3.64     | 500            |      | 5000               | 80  |                     | 25,000                | Yes      |                     | Damp             | White                  |
| BR30                                                                             |           |       |            |                 |       |           |          |                |      |                    |     |                     |                       |          |                     |                  |                        |
|  | MED       | 10    | 68160      | LED10DR303/827W | 120   | 6         | 5.4      | 700            |      | 2700               | 80  | 65W                 | 25,000                | Yes      | ★                   | Damp             | Frosted, White body    |
|                                                                                  |           |       | 68161      | LED10DR303/830W | 120   | 6         | 5.4      | 700            |      | 3000               | 80  | 65W                 | 25,000                | Yes      | ★                   | Damp             | Frosted, White body    |
|                                                                                  |           |       | 69107      | LED10DR303/850W | 120   | 6         | 5.4      | 700            |      | 3000               | 80  | 65W                 | 25,000                | Yes      | ★                   | Damp             | Frosted, White body    |
|                                                                                  |           |       | 43234      | LED10DR30V/827W | 120   | 3         | 5.37     | 650            |      | 2700               | 80  | 65W                 | 15,000                | Yes      |                     | Damp             | Frosted, White body    |
|                                                                                  |           |       | 43237      | LED10DR30V/830W | 120   | 3         | 5.37     | 650            |      | 3000               | 80  | 65W                 | 15,000                | Yes      |                     | Damp             | Frosted, White body    |
|                                                                                  |           |       | 43241      | LED10DR30V/850W | 120   | 3         | 5.37     | 650            |      | 5000               | 80  | 65W                 | 15,000                | Yes      |                     | Damp             | Frosted, White body    |
| BR40                                                                             |           |       |            |                 |       |           |          |                |      |                    |     |                     |                       |          |                     |                  |                        |
|  | MED       | 13    | 64176      | LED13DBR40/827  | 120   | 6         | 6.3      | 1070           |      | 2700               | 80  | 85W                 | 25,000                | Yes      | ★                   | Damp             | Frosted, White body    |
|                                                                                  |           |       | 14708      | LED13DBR40/830  | 120   | 6         | 6.3      | 1070           |      | 3000               | 80  | 85W                 | 25,000                | Yes      | ★                   | Damp             | Frosted, White body    |
|                                                                                  |           |       | 20445      | LED13BR40/5K/TP | 120   | 3         | 6.34     | 1070           |      | 5000               | 80  | 85W                 | 25,000                | Yes      | ★                   | Damp             | Frosted, White body    |
|                                                                                  |           |       | 69108      | LED13BR40/850   | 120   | 3         | 6.34     | 1070           |      | 5000               | 80  | 85W                 | 25,000                | Yes      | ★                   | Damp             | Coming in March        |

Directional Lamps (MR16 - GU10)

| Bulb Shape                                                                         | Base Type | Watts            | Order Code | Description       | Volts            | Case Qty** | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI    | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status   | #Location Rating | Additional Information        |                        |
|------------------------------------------------------------------------------------|-----------|------------------|------------|-------------------|------------------|------------|----------|----------------|------|--------------------|--------|---------------------|-----------------------|----------|-----------------------|------------------|-------------------------------|------------------------|
| 12 Volt AC/DC MR16                                                                 |           |                  |            |                   |                  |            |          |                |      |                    |        |                     |                       |          |                       |                  |                               |                        |
|    | GU5.3     | 7                | 93412      | LED7DMR16S830/15  | 12               | 6          | 2.3      | 460            | 3800 | 3000               | 80     | 35W                 | 25,000                | Yes      |                       | Damp             | Spot 15° beam, Silver         |                        |
|                                                                                    |           |                  | 69920      | LED7DMR16D830/25  | 12               | 6          | 1.9      | 390            | 1900 | 3000               | 83     | 35W                 | 25,000                | Yes      |                       | Damp             | Narrow Flood 25° beam, Silver |                        |
|                                                                                    |           |                  | 93433      | LED7DMR16S840/15  | 12               | 6          | 1.97     | 490            | 4200 | 4000               | 80     | 35W                 | 25,000                | Yes      |                       | Damp             | Accent, 15° beam, Silver      |                        |
|  | GU5.3     | 7                | 35195      | LED7XDMRX1683025  | 12               | 6          | 2.2      | 500            | 2350 | 3000               | 80     | 50W                 | 25,000                | Yes      | ★                     | Damp             | Narrow Flood 25° beam, White  |                        |
|                                                                                    |           |                  | 35196      | LED7XDMRX1683035  | 12               | 6          | 2.2      | 500            | 1350 | 3000               | 80     | 50W                 | 25,000                | Yes      | ★                     | Damp             | Flood 35° beam, White         |                        |
|                                                                                    |           |                  | 35206      | LED7XDMRX1682725  | 12               | 6          | 2.2      | 500            | 2350 | 2700               | 80     | 50W                 | 25,000                | Yes      | ★                     | Damp             | Narrow Flood 25° beam, White  |                        |
|                                                                                    |           |                  | 35214      | LED7XDMRX1682735  | 12               | 6          | 2.2      | 500            | 1350 | 2700               | 80     | 50W                 | 25,000                | Yes      | ★                     | Damp             | Flood 35° beam, White         |                        |
|                                                                                    |           |                  |            | 35529             | LED7DMRX16827/15 | 12         | 6        | 2.2            | 400  | 3400               | 2700   | 80                  | 35W                   | 25,000   | Yes                   |                  | Damp                          | Spot 15° beam, White   |
|                                                                                    |           |                  |            | 21359             | LED7MRX16R930/10 | 12         | 6        | 2.01           | 350  | 8000               | 3000   | 95                  | 50W                   | 25,000   | -                     |                  | Damp                          | Spot, 10° beam, Reveal |
| Value 12 Volt AC/DC MR16                                                           |           |                  |            |                   |                  |            |          |                |      |                    |        |                     |                       |          |                       |                  |                               |                        |
|  | GU5.3     | 5.5              | 35542      | LED5.5DMR1684035  | 12               | 6          | 1.8      | 460            | 1100 | 4000               | 80     | 35W                 | 25,000                | Yes      | ★                     | Damp             | Flood, 35° beam, White        |                        |
|                                                                                    |           |                  | 35535      | LED5.5DMR1683035  | 12               | 6          | 1.88     | 420            | 1000 | 3000               | 80     | 35W                 | 25,000                | Yes      | ★                     | Damp             | Flood, 35° beam, White        |                        |
|                                                                                    |           |                  | 35540      | LED5.5DMR1682735  | 12               | 6          | 1.88     | 400            | 1000 | 2700               | 80     | 35W                 | 25,000                | Yes      | ★                     | Damp             | Flood, 35° beam, White        |                        |
|                                                                                    |           |                  | 39542      | LED7XDMR16-V2725  | 12               | 6          | 1.88     | 530            | 2400 | 2700               | 80     | 50W                 | 25,000                | Yes      |                       | Damp             | Narrow Flood, 25° beam, White |                        |
|                                                                                    |           |                  | 39567      | LED7XDMR16-V2735  | 12               | 6          | 1.88     | 530            | 1400 | 2700               | 80     | 50W                 | 25,000                | Yes      |                       | Damp             | Flood, 35° beam, White        |                        |
|                                                                                    |           |                  | 35543      | LED7XDMR16-28325  | 12               | 6          | 1.8      | 500            | 2350 | 3000               | 80     | 50W                 | 25,000                | Yes      | ★                     | Damp             | Narrow Flood, 25° beam, White |                        |
|                                                                                    | 35544     | LED7XDMR16-28335 | 12         | 6                 | 1.8              | 500        | 1350     | 3000           | 80   | 50W                | 25,000 | Yes                 | ★                     | Damp     | Flood 35° beam, White |                  |                               |                        |
| 120 Volt GU10                                                                      |           |                  |            |                   |                  |            |          |                |      |                    |        |                     |                       |          |                       |                  |                               |                        |
|  | GU10      | 3.5              | 37114      | LED4D/GU1083035   | 120              | 6          | 2.1      | 250            | 550  | 3000               | 80     | 35W                 | 25,000                | Yes      | ★                     | Dry              | Flood, 35° beam, White        |                        |
|                                                                                    |           | 4                | 89020      | LED4D/GU10/NFLTP  | 120              | 3          | 2.1      | 250            | 720  | 3000               | 80     | 35W                 | 25,000                | Yes      | ★                     | Damp             | Flood, 35° beam, White        |                        |
|                                                                                    |           | 6                | 26346      | LED6D/GU10/NFL/TP | 120              | 3          | 2.1      | 380            | 1100 | 3000               | 80     | 50W                 | 25,000                | Yes      | ★                     | Damp             | Flood, 35° beam, White        |                        |

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)  
\*\* Minimum order quantity=6  
★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a "★" are not ENERGY STAR® certified.  
# UL 1993 Environmental Requirements for LED LAMPS  
Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.  
Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent on accumulation of moisture.  
Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.  
Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at  
GELighting.com/ThinkLED



## LED replacement lamps

### Directional Lamps (PAR16 - PAR20)

| Bulb Shape                                                                                                                                                           | Base Type | Watts | Order Code | Description      | Volts | Case Qty** | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information       |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|-------|------------|------------------|-------|------------|----------|----------------|------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|------------------------------|
| Compact PAR16                                                                                                                                                        |           |       |            |                  |       |            |          |                |      |                    |     |                     |                       |          |                     |                  |                              |
|                                                                                      | MED       | 4     | 26383      | LED4D/P16/NFLTP  | 120   | 3          | 2.8      | 260            | 720  | 3000               | 80  | 40W                 | 25,000                | Yes      | ★                   | Dry              | Flood, 35° beam, White       |
|                                                                                                                                                                      |           | 6     | 26384      | LED6D/P16/NFLTP  | 120   | 3          | 2.8      | 380            | 1100 | 3000               | 80  | 60W                 | 25,000                | Yes      | ★                   | Dry              | Flood, 35° beam, White       |
| Compact PAR20                                                                                                                                                        |           |       |            |                  |       |            |          |                |      |                    |     |                     |                       |          |                     |                  |                              |
| <br> | MED       | 7     | 93327      | LED7DP203B830/20 | 120   | 6          | 3.5      | 520            | 3600 | 3000               | 80  | 50W                 | 25,000                | Yes      | ★                   | Damp             | Narrow Flood, 20° beam Black |
|                                                                                                                                                                      |           |       | 93347      | LED7DP203W830/20 | 120   | 6          | 3.5      | 520            | 3600 | 3000               | 80  | 50W                 | 25,000                | Yes      | ★                   | Damp             | Narrow Flood, 20° beam White |
|                                                                                                                                                                      |           |       | 93348      | LED7DP203W830/35 | 120   | 6          | 3.5      | 520            | 1200 | 3000               | 80  | 50W                 | 25,000                | Yes      | ★                   | Damp             | Flood, 35° beam White        |
|                                                                                                                                                                      |           |       | 93349      | LED7DP203B827/20 | 120   | 6          | 3.5      | 500            | 3600 | 2700               | 80  | 50W                 | 25,000                | Yes      | ★                   | Damp             | Narrow Flood, 20° beam Black |
|                                                                                                                                                                      |           |       | 93354      | LED7DP203B827/35 | 120   | 6          | 3.5      | 500            | 1150 | 2700               | 80  | 50W                 | 25,000                | Yes      | ★                   | Damp             | Flood, 35° beam Black        |
|                                                                                                                                                                      |           |       | 93360      | LED7DP203W827/20 | 120   | 6          | 3.5      | 500            | 3600 | 2700               | 80  | 50W                 | 25,000                | Yes      | ★                   | Damp             | Narrow Flood, 20° beam White |
|                                                                                                                                                                      |           |       | 93362      | LED7DP203W827/35 | 120   | 6          | 3.5      | 500            | 1150 | 2700               | 80  | 50W                 | 25,000                | Yes      | ★                   | Damp             | Flood, 35° beam White        |

### Directional Lamps (PAR30 - Low Glare - Visual Comfort Lens™)

| Bulb Shape                                                                                                                                                              | Base Type | Watts | Order Code | Description      | Volts | Case Qty** | MOL (in) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information        |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|-------|------------|------------------|-------|------------|----------|----------------|------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|-------------------------------|
| Compact PAR30 - Low Glare - Visual Comfort Lens™                                                                                                                        |           |       |            |                  |       |            |          |                |      |                    |     |                     |                       |          |                     |                  |                               |
|                                                                                         | MED       | 12    | 84374      | LED12DP30RW93015 | 120   | 6          | 3.74     | 860            | 9400 | 3000               | 90  | 75W                 | 25,000                | Yes      | ★                   | Damp             | Spot, 15° beam, White         |
|                                                                                                                                                                         |           |       | 84379      | LED12DP30RW93025 | 120   | 6          | 3.74     | 900            | 3900 | 3000               | 90  | 75W                 | 25,000                | Yes      | ★                   | Damp             | Narrow Flood, 25° beam, White |
|                                                                                                                                                                         |           |       | 84380      | LED12DP30RW93040 | 120   | 6          | 3.74     | 900            | 1800 | 3000               | 90  | 75W                 | 25,000                | Yes      | ★                   | Damp             | Flood, 40° beam, White        |
|                                                                                                                                                                         |           |       | 84392      | LED12DP30RW92725 | 120   | 6          | 3.74     | 850            | 3500 | 2700               | 90  | 75W                 | 25,000                | Yes      | ★                   | Damp             | Narrow Flood, 25° beam, White |
|                                                                                                                                                                         |           |       | 84395      | LED12DP30RW92740 | 120   | 6          | 3.74     | 850            | 1700 | 2700               | 90  | 75W                 | 25,000                | Yes      | ★                   | Damp             | Flood, 40° beam, White        |
|                                                                                                                                                                         |           |       | 84384      | LED12DP30RW83025 | 120   | 6          | 3.74     | 1050           | 4800 | 3000               | 80  | 75W                 | 25,000                | Yes      | ★                   | Damp             | Narrow Flood, 25° beam, White |
|                                                                                                                                                                         |           |       | 42131      | LED12DP30RW83040 | 120   | 6          | 3.74     | 1050           | 2400 | 3000               | 80  | 75W                 | 25,000                | Yes      | ★                   | Damp             | Flood, 40° beam, White        |
|                                                                                                                                                                         |           |       | 42133      | LED12DP30RW82725 | 120   | 6          | 3.74     | 1000           | 4700 | 2700               | 80  | 75W                 | 25,000                | Yes      | ★                   | Damp             | Narrow Flood, 25° beam, White |
|                                                                                                                                                                         |           |       | 42134      | LED12DP30RW82740 | 120   | 6          | 3.74     | 1000           | 2200 | 2700               | 80  | 75W                 | 25,000                | Yes      | ★                   | Damp             | Flood, 40° beam, White        |
|                                                                                                                                                                         |           |       | 73583      | LED12DP30RB82740 | 120   | 6          | 3.74     | 1000           | 2200 | 2700               | 80  | 75W                 | 25,000                | Yes      | ★                   | Damp             | Flood, 40° beam, Black        |
| Compact PAR30 - Long Neck - Low Glare - Visual Comfort Lens™                                                                                                            |           |       |            |                  |       |            |          |                |      |                    |     |                     |                       |          |                     |                  |                               |
| <br> | MED       | 12    | 84399      | LED12DP3LRW93025 | 120   | 6          | 4.72     | 900            | 3900 | 3000               | 90  | 75W                 | 25,000                | Yes      | ★                   | Damp             | Narrow Flood, 25° beam, White |
|                                                                                                                                                                         |           |       | 84400      | LED12DP3LRW93040 | 120   | 6          | 4.72     | 900            | 1800 | 3000               | 90  | 75W                 | 25,000                | Yes      | ★                   | Damp             | Flood, 40° beam, White        |
|                                                                                                                                                                         |           |       | 84407      | LED12DP3LRW92740 | 120   | 6          | 4.72     | 850            | 1700 | 2700               | 90  | 75W                 | 25,000                | Yes      | ★                   | Damp             | Flood, 40° beam, White        |
|                                                                                                                                                                         |           |       | 42136      | LED12DP3LRW83025 | 120   | 6          | 4.72     | 1050           | 4800 | 3000               | 80  | 75W                 | 25,000                | Yes      | ★                   | Damp             | Narrow Flood, 25° beam, White |
|                                                                                                                                                                         |           |       | 42137      | LED12DP3LRW83040 | 120   | 6          | 4.72     | 1050           | 2400 | 3000               | 80  | 75W                 | 25,000                | Yes      | ★                   | Damp             | Flood, 40° beam, White        |
|                                                                                                                                                                         |           |       | 42141      | LED12DP3LRW82725 | 120   | 6          | 4.72     | 1000           | 4700 | 2700               | 80  | 75W                 | 25,000                | Yes      | ★                   | Damp             | Narrow Flood, 25° beam, White |
|                                                                                                                                                                         |           |       | 42144      | LED12DP3LRW82740 | 120   | 6          | 4.72     | 1000           | 2200 | 2700               | 80  | 75W                 | 25,000                | Yes      | ★                   | Damp             | Flood, 40° beam, White        |
|                                                                                                                                                                         |           |       | 20151      | LED17DP30LW93025 | 120   | 6          | 4.8      | 1100           | 4600 | 3000               | 90  | 75W                 | 25,000                | Yes      | ★                   | Damp             | Spot, 25° beam, White         |

### Directional Lamps (PAR30 - STIR)

| Bulb Shape                                                                         | Base Type | Watts | Order Code | Description      | Volts | Case Qty** | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information        |
|------------------------------------------------------------------------------------|-----------|-------|------------|------------------|-------|------------|----------|----------------|------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|-------------------------------|
| Compact PAR30                                                                      |           |       |            |                  |       |            |          |                |      |                    |     |                     |                       |          |                     |                  |                               |
|  | MED       | 12    | 98755      | LED12DP303W83035 | 120   | 6          | 3.66     | 950            | 2600 | 3000               | 80  | 75W                 | 25,000                | Yes      | ★                   | Damp             | Flood, 35° beam, White, STIR  |
| Compact PAR30 Long Neck                                                            |           |       |            |                  |       |            |          |                |      |                    |     |                     |                       |          |                     |                  |                               |
|  | MED       | 12    | 98811      | LED12DP3L3W83035 | 120   | 6          | 4.61     | 950            | 2600 | 3000               | 80  | 75W                 | 25,000                | Yes      | ★                   | Damp             | Accent, 35° beam, White, STIR |

### Directional Lamps (PAR30 - High Output)

| Bulb Shape                                                                         | Base Type | Watts | Order Code | Description     | Volts   | Case Qty** | MOL (In) | Lumens Initial | CBCP  | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information                                       |
|------------------------------------------------------------------------------------|-----------|-------|------------|-----------------|---------|------------|----------|----------------|-------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|--------------------------------------------------------------|
| Universal 120-277V                                                                 |           |       |            |                 |         |            |          |                |       |                    |     |                     |                       |          |                     |                  |                                                              |
|  | MED       | 18    | 75089      | LED18P30LW83015 | 120-277 | 6          | 4.6      | 1800           | 15500 | 3000               | 80  | 75W                 | 25,000                | -        |                     | Damp             | Spot, 15°, White                                             |
|                                                                                    |           |       | 75091      | LED18P30LW83025 | 120-277 | 6          | 4.6      | 1800           | 7000  | 3000               | 80  | 75W                 | 25,000                | -        |                     | Damp             | Narrow Flood, 25°, White                                     |
|                                                                                    |           |       | 75065      | LED18P30LW93015 | 120-277 | 6          | 4.6      | 1400           | 12500 | 3000               | 90  | 75W                 | 25,000                | -        |                     | Damp             | Spot, 15° beam, MTO, 1000 Min. Qty, 12 Week Lead Time, White |
|                                                                                    |           |       | 75078      | LED18P30LW93025 | 120-277 | 6          | 4.6      | 1400           | 5000  | 3000               | 90  | 75W                 | 25,000                | -        |                     | Damp             | Narrow Flood, 25°, White                                     |

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

\*\* Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

# UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at  
[GELighting.com/ThinkLED](http://GELighting.com/ThinkLED)

LED replacement lamps

Reveal® Whiter White Technology - PAR30

| Bulb Shape                                                                       | Base Type | Watts | Order Code | Description     | Volts | Case Qty** | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information                                        |
|----------------------------------------------------------------------------------|-----------|-------|------------|-----------------|-------|------------|----------|----------------|------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|---------------------------------------------------------------|
| reveal® Whiter White Technology - PAR30                                          |           |       |            |                 |       |            |          |                |      |                    |     |                     |                       |          |                     |                  |                                                               |
|  |           | 18    | 28274      | LED12D30WW93015 | 120   | 6          | 3.74     | 650            | 6000 | 3000               | 91  | -                   | 25,000                | Yes      |                     | Damp             | Spot, 15° beam, White, MTO, 1000 Min. Qty, 12 Week Lead Time, |
|                                                                                  |           |       | 28275      | LED12D30WW93025 | 120   | 6          | 3.74     | 650            | 2500 | 3000               | 91  | -                   | 25,000                | Yes      |                     | Damp             | Narrow Flood, 25° beam, White                                 |

Directional Lamps (PAR38 - Low Glare - Visual Comfort Lens™)

| Bulb Shape                                                                       | Base Type | Watts | Order Code | Description      | Volts | Case Qty** | MOL (In) | Lumens Initial | CBCP  | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information        |
|----------------------------------------------------------------------------------|-----------|-------|------------|------------------|-------|------------|----------|----------------|-------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|-------------------------------|
| PAR38 - Low Glare - Visual Comfort Lens™                                         |           |       |            |                  |       |            |          |                |       |                    |     |                     |                       |          |                     |                  |                               |
|  |           | 12    | 63323      | LED12DP38W827/25 | 120   | 6          | 5.3      | 960            | 4600  | 2700               | 80  | 90W                 | 25,000                | Yes      |                     | Dry              | Narrow Flood, 25° beam, White |
|                                                                                  |           |       | 63334      | LED12DP38W927/25 | 120   | 6          | 5.3      | 820            | 3900  | 2700               | 91  | 90W                 | 25,000                | Yes      |                     | Dry              | Narrow Flood, 25° beam, White |
|  |           |       | 63330      | LED12DP38W930/15 | 120   | 6          | 5.32     | 860            | 11400 | 3000               | 91  | 90W                 | 25,000                | Yes      |                     | Dry              | Narrow Flood, 15° beam, White |
|                                                                                  |           |       | 92971      | LED12D38W3827/40 | 120   | 6          | 5.31     | 1050           | 2300  | 2700               | 81  | 100W                | 25,000                | Yes      | ★                   | Damp             | Flood, 40° beam, White        |
|  |           |       | 92972      | LED12D38W3830/25 | 120   | 6          | 5.31     | 1050           | 5500  | 3000               | 81  | 100W                | 25,000                | Yes      | ★                   | Damp             | Narrow Flood, 25° beam, White |
|                                                                                  |           |       | 92973      | LED12D38W3830/40 | 120   | 6          | 5.31     | 1050           | 2300  | 3000               | 80  | 100W                | 25,000                | Yes      | ★                   | Wet              | Flood, 40° beam, White        |
|  |           | 18    | 92923      | LED18D38W3927/25 | 120   | 6          | 5.31     | 1250           | 4900  | 2700               | 92  | 100W                | 25,000                | Yes      | ★                   | Damp             | Narrow Flood, 25° beam, White |
|                                                                                  |           |       | 92933      | LED18D38W3930/25 | 120   | 6          | 5.31     | 1350           | 5200  | 3000               | 92  | 100W                | 25,000                | Yes      | ★                   | Damp             | Narrow Flood, 25° beam, White |
|  |           |       | 92927      | LED18D38W3930/15 | 120   | 6          | 5.32     | 1350           | 15000 | 3000               | 92  | 75W                 | 25,000                | Yes      | ★                   | Wet              | Spot, 15° beam, White         |
|                                                                                  |           |       | 92934      | LED18D38W3930/40 | 120   | 6          | 5.12     | 1350           | 3200  | 3000               | 92  | 120W                | 25,000                | Yes      | ★                   | Damp             | Flood, 40° beam, White        |
|  |           |       | 92950      | LED18D38W3827/25 | 120   | 6          | 5.12     | 1550           | 5800  | 2700               | 81  | 120W                | 25,000                | Yes      | ★                   | Wet              | Narrow Flood, 25° beam, White |
|                                                                                  |           |       | 92958      | LED18D38W3827/40 | 120   | 6          | 5.12     | 1550           | 3800  | 2700               | 81  | 120W                | 25,000                | Yes      | ★                   | Wet              | Flood, 40° beam, White        |
|  |           |       | 92961      | LED18D38W3830/15 | 120   | 6          | 5.12     | 1750           | 20000 | 3000               | 81  | 150W                | 25,000                | Yes      | ★                   | Wet              | Spot, 15° beam, White         |
|                                                                                  |           |       | 92963      | LED18D38W3830/25 | 120   | 6          | 5.12     | 1550           | 6000  | 3000               | 81  | 120W                | 25,000                | Yes      | ★                   | Wet              | Narrow Flood, 25° beam, White |
|  |           |       | 92967      | LED18D38W3830/40 | 120   | 6          | 5.12     | 1550           | 4000  | 3000               | 81  | 150W                | 25,000                | Yes      | ★                   | Wet              | Flood, 40° beam, White        |
|                                                                                  |           |       | 92926      | LED18D38W3927/40 | 120   | 6          | 5.12     | 1250           | 2900  | 2700               | 92  | 120W                | 25,000                | Yes      | ★                   | Damp             | Flood, 40° beam, White        |
|  |           |       | 93172      | LED18D38W3840/40 | 120   | 6          | 5.31     | 1700           | 4400  | 4000               | 81  | 150W                | 25,000                | Yes      | ★                   | Wet              | Flood, 40° beam, White        |
|                                                                                  |           |       | 65730      | LED18D38W3850/25 | 120   | 6          | 5.31     | 1700           | 6500  | 5000               | 81  | 120W                | 25,000                | Yes      | ★                   | Wet              | Narrow Flood, 25° beam, White |
|  |           |       | 65731      | LED18D38W3850/40 | 120   | 6          | 5.31     | 1700           | 4400  | 5000               | 81  | 150W                | 25,000                | Yes      | ★                   | Wet              | Flood, 40° beam, White        |
|                                                                                  |           |       | 93171      | LED18D38W3840/25 | 120   | 6          | 5.31     | 1700           | 6500  | 4000               | 81  | 120W                | 25,000                | Yes      | ★                   | Wet              | Narrow Flood, 25° beam, White |
|  |           |       | 85085      | LED18D38W3835/25 | 120   | 6          | 5.31     | 1700           | 6500  | 3500               | 81  | 120W                | 25,000                | Yes      | ★                   | Wet              | Narrow Flood, 25° beam, White |
|                                                                                  |           |       | 87917      | LED18D38W3835/40 | 120   | 6          | 5.31     | 1700           | 4400  | 3500               | 81  | 150W                | 25,000                | Yes      | ★                   | Wet              | Flood, 40° beam, White        |

Reveal® Whiter White Technology - PAR38

| Bulb Shape                                                                         | Base Type | Watts | Order Code | Description      | Volts | Case Qty** | MOL (In) | Lumens Initial | CBCP  | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information                                       |
|------------------------------------------------------------------------------------|-----------|-------|------------|------------------|-------|------------|----------|----------------|-------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|--------------------------------------------------------------|
| reveal® Whiter White Technology - PAR38                                            |           |       |            |                  |       |            |          |                |       |                    |     |                     |                       |          |                     |                  |                                                              |
|  |           | 18    | 31300      | LED18D38WW930/15 | 120   | 6          | 5.31     | 1170           | 10000 | 3000               | 91  | 100W                | 25,000                | Yes      | ★                   | Damp             | Spot, 15° beam, White, MTO, 1000 Min. Qty, 12 Week Lead Time |
|                                                                                    |           |       | 31301      | LED18D38WW930/25 | 120   | 6          | 5.31     | 1170           | 4500  | 3000               | 91  | 100W                | 25,000                | Yes      | ★                   | Damp             | Narrow Flood, 25° beam, White                                |

Directional Lamps (Commercial PAR38)

| Bulb Shape                                                                         | Base Type | Watts | Order Code | Description       | Volts | Case Qty** | MOL (In) | Lumens Initial | CBCP   | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information                  |
|------------------------------------------------------------------------------------|-----------|-------|------------|-------------------|-------|------------|----------|----------------|--------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|-----------------------------------------|
| Commercial PAR38 (Indoor/Outdoor)                                                  |           |       |            |                   |       |            |          |                |        |                    |     |                     |                       |          |                     |                  |                                         |
|  |           | 12    | 90132      | LED12DP382W827/25 | 120   | 6          | 5.1      | 850            | 4000   | 2700               | 84  | 85W                 | 25,000                | Yes      |                     | Wet              | Narrow Flood, 25° beam, White           |
|                                                                                    |           | 26    | 68183      | LED26DP38S830/12  | 120   | 6          | 5.3      | 1500           | 24000  | 3000               | 82  | 130W                | 25,000                | Yes      | ★                   | Wet              | Spot, 12° beam, Silver                  |
|  |           |       | 68184      | LED26DP38S830/25  | 120   | 6          | 5.3      | 1500           | 6800   | 3000               | 82  | 130W                | 25,000                | Yes      | ★                   | Wet              | Narrow Flood, 25° beam, Silver          |
|                                                                                    |           |       | 68185      | LED26DP38S830/40  | 120   | 6          | 5.3      | 1500           | 3100   | 3000               | 82  | 120W                | 25,000                | Yes      | ★                   | Wet              | Flood, 40° beam, Silver                 |
|  |           |       | 68182      | LED26DP38S840/40  | 120   | 6          | 5.3      | 1650           | 3200   | 4000               | 82  | 120W                | 25,000                | Yes      |                     | Wet              | Flood, 40° beam, Silver                 |
|                                                                                    |           |       | 33647      | LED26DP38S835/12  | 120   | 6          | 5.3      | 1900           | 31000  | 3500               | 82  | 160W                | 25,000                | Yes      | ★                   | Wet              | Spot, 12° beam, Silver                  |
|  |           |       | 70591      | LED26DP38S835/40  | 120   | 6          | 5.3      | 1900           | 4000   | 3500               | 82  | 160W                | 25,000                | Yes      | ★                   | Wet              | Flood, 40° beam, Silver                 |
|                                                                                    |           | 28    | 15139      | LED28P38S830/15   | 120   | 6          | 5.3      | 2400           | 20000  | 3000               | 81  | 150W                | 25,000                | -        | ★                   | Damp             | Spot, 15° beam, Silver, Non-Dimming     |
|  |           |       | 25844      | LED28P38S830/25   | 120   | 6          | 5.31     | 2400           | 11000  | 3000               | 81  | 150W                | 25,000                | -        | ★                   | Damp             | Narrow Flood, 25° beam, Silver, Non-Dim |
|                                                                                    |           |       | 25953      | LED28P38S830/40   | 120   | 6          | 5.31     | 2400           | 5,600  | 3000               | 81  | 150W                | 25,000                | -        | ★                   | Damp             | Flood, 40° beam, Silver, Non-Dimming    |
|  |           |       | 75447      | LED32DP38W830/15  | 120   | 6          | 5.12     | 3000           | 26,000 | 3000               | 81  | 250W                | 25,000                | Yes      |                     | Wet              | Coming in March                         |
|                                                                                    |           |       | 88801      | LED32DP38W830/25  | 120   | 6          | 5.12     | 3000           | 13,000 | 3000               | 81  | 250W                | 25,000                | Yes      |                     | Wet              | Coming in March                         |
|  |           |       | 88810      | LED32DP38W830/40  | 120   | 6          | 5.12     | 3000           | 6,000  | 3000               | 81  | 250W                | 25,000                | Yes      |                     | Wet              | Coming in March                         |

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

\*\* Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

# UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "7TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at  
[GELighting.com/ThinkLED](http://GELighting.com/ThinkLED)

LED replacement lamps

Directional Lamps (PAR38 - STIR)

| Bulb Shape              | Base Type | Watts | Order Code | Description      | Volts | Case Qty" | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information       |
|-------------------------|-----------|-------|------------|------------------|-------|-----------|----------|----------------|------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|------------------------------|
| Single Optics 15W PAR38 |           |       |            |                  |       |           |          |                |      |                    |     |                     |                       |          |                     |                  |                              |
| PAR38                   | MED       | 15    | 32213      | LED15DP38W830/40 | 120   | 6         | 5.04     | 1300           | 2300 | 3000               | 81  | 90W                 | 25,000                | Yes      | ★                   | Wet              | Flood, 40° beam, White, STIR |

LED HID

| Bulb Shape                                                                       | Base Type | Watts | Order Code | Description      | Volts | Case Qty" | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information                            |
|----------------------------------------------------------------------------------|-----------|-------|------------|------------------|-------|-----------|----------|----------------|------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|---------------------------------------------------|
| 400 Watt Metal Halide Replacement Lamp                                           |           |       |            |                  |       |           |          |                |      |                    |     |                     |                       |          |                     |                  |                                                   |
|  | EX39      | 165   | 21259      | LED165/M400/740  |       | 3         | 11.42    | 20,000         |      | 4000               | 73  | 400                 | 50,000                | -        |                     | Dry              | Open Rated, CWA, ANSI - M59, M135, M155           |
|                                                                                  |           | 130   | 43252      | LED130/2M400/740 |       | 3         | 8.4      | 18,500         |      | 4000               | 70  | 400W                | 50,000                | -        |                     | Damp             | Available March                                   |
|                                                                                  |           |       | 88109      | LED130/2M400/750 |       | 3         | 8.4      | 18,500         |      | 5000               | 70  | 400W                | 50,000                | -        |                     | Damp             | Available March                                   |
|                                                                                  |           | 80    | 43258      | LED80/2M250/740  |       | 3         | 8.4      | 11,800         |      | 4000               | 70  | 250W                | 50,000                | -        |                     | Damp             | Open or Enclosed Rated, CWA ANSI -M58, M138, M153 |
|  |           |       | 88099      | LED80/2M250/750  |       | 3         | 8.4      | 11,800         |      | 5000               | 70  | 250W                | 50,000                | -        |                     | Damp             | Open or Enclosed Rated, CWA ANSI -M58, M138, M153 |
|                                                                                  |           | 60    | 43263      | LED60/2M175/740  |       | 3         | 8.4      | 8,800          |      | 4000               | 70  | 175W                | 50,000                | -        |                     | Damp             | Open or Enclosed Rated, CWA ANSI -M57, M137, M152 |
|                                                                                  |           |       | 88107      | LED60/2M175/750  |       | 3         | 8.4      | 8,800          |      | 5000               | 70  | 175W                | 50,000                | -        |                     | Damp             | Open or Enclosed Rated, CWA ANSI -M57, M137, M152 |
|                                                                                  |           |       |            |                  |       |           |          |                |      |                    |     |                     |                       |          |                     |                  |                                                   |

Plug-In

| Bulb Shape                                                                         | Base Type | Watts     | Order Code | Description | Volts            | Case Qty" | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI  | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | #Location Rating | Additional Information             |
|------------------------------------------------------------------------------------|-----------|-----------|------------|-------------|------------------|-----------|----------|----------------|------|--------------------|------|---------------------|-----------------------|----------|------------------|------------------------------------|
| Vertical                                                                           |           |           |            |             |                  |           |          |                |      |                    |      |                     |                       |          |                  |                                    |
|  | Plug-In   | G24q/GX24 | 12         | 96801       | LED12G24Q-V/827  | #         | 6        | 5.31           | 950  | 2700               | 80   |                     | 50000                 | -        | Damp             | Requires Electronic Ballast, White |
|                                                                                    |           |           |            | 96775       | LED12G24Q-V/830  | #         | 6        | 5.31           | 950  | 3000               | 80   |                     | 50000                 | -        | Damp             | Requires Electronic Ballast, White |
|                                                                                    |           |           |            | 96689       | LED12G24Q-V/835  | #         | 6        | 5.31           | 1000 | 3500               | 80   |                     | 50000                 | -        | Damp             | Requires Electronic Ballast, White |
|                                                                                    |           |           |            | 96771       | LED12G24Q-V/840  | #         | 6        | 5.31           | 1000 | 4000               | 80   |                     | 50000                 | -        | Damp             | Requires Electronic Ballast, White |
|                                                                                    |           | GX24q     | 18.5       | 39288       | LED19GX24q-V/827 | #         | 6        | 6.42           | 1800 | 2700               | 80   |                     | 50000                 | -        | Damp             | Requires Electronic Ballast, White |
|                                                                                    |           |           |            | 39277       | LED19GX24q-V/830 | #         | 6        | 6.42           | 1850 | -                  | 3000 | 80                  | 50000                 | -        | Damp             | Requires Electronic Ballast, White |
|                                                                                    |           |           |            | 39275       | LED19GX24q-V/835 | #         | 6        | 6.42           | 1950 | -                  | 3500 | 80                  | 50000                 | -        | Damp             | Requires Electronic Ballast, White |
|                                                                                    |           |           |            | 39279       | LED19GX24q-V/840 | #         | 6        | 6.42           | 1950 | -                  | 4000 | 80                  | 50000                 | -        | Damp             | Requires Electronic Ballast, White |
| Horizontal                                                                         |           |           |            |             |                  |           |          |                |      |                    |      |                     |                       |          |                  |                                    |
|  | Plug-In   | G24q/GX24 | 12         | 96799       | LED12G24Q-H/827  | #         | 6        | 5.31           | 950  | 2700               | 80   |                     | 50000                 | -        | Damp             | Requires Electronic Ballast, White |
|                                                                                    |           |           |            | 96798       | LED12G24Q-H/830  | #         | 6        | 5.31           | 950  | 3000               | 80   |                     | 50000                 | -        | Damp             | Requires Electronic Ballast, White |
|                                                                                    |           |           |            | 96761       | LED12G24Q-H/835  | #         | 6        | 5.31           | 1000 | 3500               | 80   |                     | 50000                 | -        | Damp             | Requires Electronic Ballast, White |
|                                                                                    |           |           |            | 96769       | LED12G24Q-H/840  | #         | 6        | 5.31           | 1000 | 4000               | 80   |                     | 50000                 | -        | Damp             | Requires Electronic Ballast, White |
|                                                                                    |           | GX24q     | 18.5       | 39289       | LED19GX24q-H/827 | #         | 6        | 6.7            | 1800 | 2700               | 80   |                     | 50000                 | -        | Damp             | Requires Electronic Ballast, White |
|                                                                                    |           |           |            | 39282       | LED19GX24q-H/830 | #         | 6        | 6.7            | 1850 | 3000               | 80   |                     | 50000                 | -        | Damp             | Requires Electronic Ballast, White |
|                                                                                    |           |           |            | 39276       | LED19GX24q-H/835 | #         | 6        | 6.7            | 1950 | 3500               | 80   |                     | 50000                 | -        | Damp             | Requires Electronic Ballast, White |
|                                                                                    |           |           |            | 39283       | LED19GX24q-H/840 | #         | 6        | 6.7            | 1950 | 4000               | 80   |                     | 50000                 | -        | Damp             | Requires Electronic Ballast, White |

# - Check compatibility at [GELighting.com/LED4pin-compatibility](https://www.gelighting.com/LED4pin-compatibility)

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

\*\* Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

# UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at  
[GELighting.com/ThinkLED](https://www.gelighting.com/ThinkLED)



LED replacement tubes

High Lumen Biax

| Bulb Shape                                                                       | Base Type | Watts | Order Code | Description      | Volts | Case Qty" | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | #Location Rating | Additional Information                 |
|----------------------------------------------------------------------------------|-----------|-------|------------|------------------|-------|-----------|----------|----------------|------|--------------------|-----|---------------------|-----------------------|----------|------------------|----------------------------------------|
| High Lumen Biax (HLBX)                                                           |           |       |            |                  |       |           |          |                |      |                    |     |                     |                       |          |                  |                                        |
|  | 2G11      | 17    | 39073      | LED172G11/830/10 | #     | 10        | 22.3     | 2150           |      | 3000               | 80  |                     | 40000                 | -        | Damp             | Indoor, White, Instant/PS Ballast      |
|                                                                                  |           |       | 39074      | LED172G11/835/10 | #     | 10        | 22.3     | 2150           |      | 3500               | 80  |                     | 40000                 | -        | Damp             | Indoor, White, Instant/PS Ballast      |
|                                                                                  |           |       | 39075      | LED172G11/840/10 | #     | 10        | 22.3     | 2200           |      | 4000               | 80  |                     | 40000                 | -        | Damp             | Indoor, White, Instant/PS Ballast      |
|                                                                                  |           |       | 39076      | LED172G11/850/10 | #     | 10        | 22.3     | 2200           |      | 5000               | 80  |                     | 40000                 | -        | Damp             | MTO, 1000 Min. Qty., 12 Week Lead Time |

# - Check compatibility at [GELighting.com/LED2G11-compatibility](http://GELighting.com/LED2G11-compatibility)

RS Cans

| Bulb Shape                                                                       | Base Type | Watts | Order Code | Description      | Volts | Case Qty" | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information     |
|----------------------------------------------------------------------------------|-----------|-------|------------|------------------|-------|-----------|----------|----------------|------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|----------------------------|
| RS Cans                                                                          |           |       |            |                  |       |           |          |                |      |                    |     |                     |                       |          |                     |                  |                            |
|  | E26       | 10    | 95853      | LED10RS4/827E26P | 120   | 12        | 5.88     | 700            |      | 2700               | 80  | 65W                 | 50,000                | Yes      | ★                   | Damp             | 4" Can, Pigtail Attachment |
|                                                                                  |           |       | 95854      | LED10RS4/830E26P | 120   | 12        | 5.88     | 700            |      | 3000               | 80  | 65W                 | 50,000                | Yes      | ★                   | Damp             | 4" Can, Pigtail Attachment |
|                                                                                  |           |       | 35365      | LED10RS4/840E26P | 120   | 12        | 7.5      | 700            |      | 4000               | 80  | 65W                 | 50,000                | Yes      | ★                   | Damp             | 4" Can, Pigtail Attachment |
|                                                                                  | GU24      |       | 95855      | LED10RS4/827GUP  | 120   | 12        | 5.88     | 700            |      | 2700               | 80  | 65W                 | 50,000                | Yes      | ★                   | Damp             | 4" Can, Pigtail Attachment |
|                                                                                  |           |       | 95856      | LED10RS4/830GUP  | 120   | 12        | 5.88     | 700            |      | 3000               | 80  | 65W                 | 50,000                | Yes      | ★                   | Damp             | 4" Can, Pigtail Attachment |
|                                                                                  | E26       |       | 85153      | LED10RS6/827E26P | 120   | 12        | 7.5      | 700            |      | 2700               | 80  | 65W                 | 50,000                | Yes      | ★                   | Damp             | 6" Can, Pigtail Attachment |
|                                                                                  |           |       | 85160      | LED10RS6/830E26P | 120   | 12        | 7.5      | 700            |      | 3000               | 80  | 65W                 | 50,000                | Yes      | ★                   | Damp             | 6" Can, Pigtail Attachment |
|                                                                                  |           |       | 30367      | LED10RS6/840E26P | 120   | 12        | 7.5      | 700            |      | 4000               | 80  | 65W                 | 50,000                | Yes      | ★                   | Damp             | 6" Can, Pigtail Attachment |
|                                                                                  | GU24      |       | 95851      | LED10RS6/827GUP  | 120   | 12        | 7.5      | 700            |      | 2700               | 80  | 65W                 | 50,000                | Yes      | ★                   | Damp             | 6" Can, Pigtail Attachment |
|                                                                                  |           |       | 95852      | LED10RS6/830GUP  | 120   | 12        | 7.5      | 700            |      | 3000               | 80  | 65W                 | 50,000                | Yes      | ★                   | Damp             | 6" Can, Pigtail Attachment |
|                                                                                  | E26       | 13    | 70120      | LED13RS6/827E26P | 120   | 12        | 7.5      | 1000           |      | 2700               | 80  | 90W                 | 50,000                | Yes      | ★                   | Damp             | 6" Can, Pigtail Attachment |
|                                                                                  |           |       | 70122      | LED13RS6/830E26P | 120   | 12        | 7.5      | 1000           |      | 3000               | 80  | 90W                 | 50,000                | Yes      | ★                   | Damp             | 6" Can, Pigtail Attachment |
|                                                                                  | GU24      |       | 70124      | LED13RS6/827GUP  | 120   | 12        | 7.5      | 1000           |      | 2700               | 80  | 90W                 | 50,000                | Yes      | ★                   | Damp             | 6" Can, Pigtail Attachment |
|                                                                                  |           |       | 70127      | LED13RS6/830GUP  | 120   | 12        | 7.5      | 1000           |      | 3000               | 80  | 90W                 | 50,000                | Yes      | ★                   | Damp             | 6" Can, Pigtail Attachment |

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)  
\*\* Minimum order quantity = 6

# UL 1993 Environmental Requirements for LED LAMPS  
Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.  
Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.  
Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.  
Notes: 1) Product descriptions ending in "7TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at  
[GELighting.com/ThinkLED](http://GELighting.com/ThinkLED)

# LED replacement lamps

## Integrated Plastic Tubes - Type A

| Type                                                                                  | Base Type | Watts | Order Code | Description     | Volts | Case Qty | MOL (in) | Lumens Initial | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | DLC | UL  | #Location Rating | Additional Information |
|---------------------------------------------------------------------------------------|-----------|-------|------------|-----------------|-------|----------|----------|----------------|--------------------|-----|---------------------|-----------------------|-----|-----|------------------|------------------------|
| Integrated 4ft LED Plastic Tubes (operates on Instant Start or Program Start Ballast) |           |       |            |                 |       |          |          |                |                    |     |                     |                       |     |     |                  |                        |
| T8                                                                                    | G13       | 18    | 31550      | LED18ET8/4/830  | 25    | 48       | 2150     | 3000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                       | G13       | 18    | 93133      | LED18ET8/4/835  | 25    | 48       | 2250     | 3500K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                       | G13       | 18    | 93135      | LED18ET8/4/840  | 25    | 48       | 2250     | 4000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                       | G13       | 18    | 93140      | LED18ET8/4/850  | 25    | 48       | 2350     | 5000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                       | G13       | 15    | 62399      | LED15ET8/4/830  | 25    | 48       | 1850     | 3000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                       | G13       | 15    | 62401      | LED15ET8/4/835  | 25    | 48       | 1950     | 3500K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                       | G13       | 15    | 62402      | LED15ET8/4/840  | 25    | 48       | 1950     | 4000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                       | G13       | 15    | 62409      | LED15ET8/4/850  | 25    | 48       | 2050     | 5000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                       | G13       | 15    | 62410      | LED15ET8/4/865  | 25    | 48       | 1950     | 6500K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Instant or PRS Ballast |
|                                                                                       | G13       | 12    | 61218      | LED12ET8/4/830  | 25    | 48       | 1550     | 3000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                       | G13       | 12    | 61223      | LED12ET8/4/835  | 25    | 48       | 1600     | 3500K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                       | G13       | 12    | 61271      | LED12ET8/4/840  | 25    | 48       | 1600     | 4000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                       | G13       | 12    | 61327      | LED12ET8/4/850  | 25    | 48       | 1700     | 5000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                       | G13       | 12    | 61329      | LED12ET8/4/865  | 25    | 48       | 1600     | 6500K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Instant or PRS Ballast |
| Integrated 3ft LED Plastic Tubes (operates on Instant Start or Program Start Ballast) |           |       |            |                 |       |          |          |                |                    |     |                     |                       |     |     |                  |                        |
|                                                                                       | G13       | 12    | 31554      | LED12ET8/3/830  | 25    | 36       | 1350     | 3000K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Instant or PRS Ballast |
|                                                                                       | G13       | 12    | 26544      | LED12ET8/3/835  | 25    | 36       | 1400     | 3500K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Instant or PRS Ballast |
|                                                                                       | G13       | 12    | 26625      | LED12ET8/3/840  | 25    | 36       | 1400     | 4000K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Instant or PRS Ballast |
|                                                                                       | G13       | 12    | 26627      | LED12ET8/3/850  | 25    | 36       | 1500     | 5000K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Instant or PRS Ballast |
| Integrated 2ft LED Plastic Tubes (operates on Instant Start or Program Start Ballast) |           |       |            |                 |       |          |          |                |                    |     |                     |                       |     |     |                  |                        |
|                                                                                       | G13       | 9     | 31557      | LED9ET8/2/830   | 25    | 24       | 1100     | 3000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                       | G13       | 9     | 26635      | LED9ET8/2/835   | 25    | 24       | 1100     | 3500K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                       | G13       | 9     | 26648      | LED9ET8/2/840   | 25    | 24       | 1100     | 4000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                       | G13       | 9     | 26676      | LED9ET8/2/850   | 25    | 24       | 1100     | 5000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
| Integrated U6 Plastic Tubes                                                           |           |       |            |                 |       |          |          |                |                    |     |                     |                       |     |     |                  |                        |
|                                                                                       | G13       | 13    | 43120      | LED13ET8/U6/830 | 12    | 22.5     | 1800     | 3000K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Instant or PRS Ballast |
|                                                                                       | G13       | 13    | 43125      | LED13ET8/U6/835 | 12    | 22.5     | 1850     | 3500K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Instant or PRS Ballast |
|                                                                                       | G13       | 13    | 43129      | LED13ET8/U6/840 | 12    | 22.5     | 1900     | 4000K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Instant or PRS Ballast |
|                                                                                       | G13       | 13    | 43130      | LED13ET8/U6/850 | 12    | 22.5     | 1900     | 5000K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Instant or PRS Ballast |

### Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

\*\* Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

# UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at  
[GELighting.com/ThinkLED](http://GELighting.com/ThinkLED)

LED replacement tubes

Integrated Glass Tubes - Type A

| Type                                                                                       | Base Type | Watts | Order Code | Description      | Volts | Case Qty** | MOL (In) | Lumens Initial | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | DLC | UL  | #Location Rating | Additional Information |
|--------------------------------------------------------------------------------------------|-----------|-------|------------|------------------|-------|------------|----------|----------------|--------------------|-----|---------------------|-----------------------|-----|-----|------------------|------------------------|
| Integrated 4 ft LED Glass Tubes (operates on Instant Start or Program Start Ballast)       |           |       |            |                  |       |            |          |                |                    |     |                     |                       |     |     |                  |                        |
| T8                                                                                         | G13       | 18    | 35767      | LED18ET8/G/4/830 |       | 20         | 48       | 2200           | 3000K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                            | G13       | 18    | 35768      | LED18ET8/G/4/835 |       | 20         | 48       | 2300           | 3500K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                            | G13       | 18    | 35769      | LED18ET8/G/4/840 |       | 20         | 48       | 2300           | 4000K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                            | G13       | 18    | 35772      | LED18ET8/G/4/850 |       | 20         | 48       | 2400           | 5000K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                            | G13       | 18    | 35773      | LED18ET8/G/4/865 |       | 20         | 48       | 2300           | 6500K              | 80+ |                     | 50,000                | -   | Yes | Damp             | Instant or PRS Ballast |
|                                                                                            | G13       | 15    | 35790      | LED15ET8/G/4/830 |       | 20         | 48       | 1900           | 3000K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                            | G13       | 15    | 35791      | LED15ET8/G/4/835 |       | 20         | 48       | 2000           | 3500K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                            | G13       | 15    | 35793      | LED15ET8/G/4/840 |       | 20         | 48       | 2000           | 4000K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                            | G13       | 15    | 35797      | LED15ET8/G/4/850 |       | 20         | 48       | 2100           | 5000K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                            | G13       | 15    | 35798      | LED15ET8/G/4/865 |       | 20         | 48       | 2000           | 6500K              | 80+ |                     | 50,000                | -   | Yes | Damp             | Instant or PRS Ballast |
|                                                                                            | G13       | 12    | 43284      | LED12ET8/G/4/830 |       | 20         | 48       | 1600           | 3000K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                            | G13       | 12    | 43288      | LED12ET8/G/4/835 |       | 20         | 48       | 1650           | 3500K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                            | G13       | 12    | 43291      | LED12ET8/G/4/840 |       | 20         | 48       | 1650           | 4000K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                            | G13       | 12    | 43293      | LED12ET8/G/4/850 |       | 20         | 48       | 1750           | 5000K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
| Integrated 4 ft Value LED Glass Tubes (operates on Instant Start or Program Start Ballast) |           |       |            |                  |       |            |          |                |                    |     |                     |                       |     |     |                  |                        |
| T8                                                                                         | G13       | 15    | 35896      | LED15ET8/835-V6P |       | 6          | 48       | 1750           | 3500K              | 80+ |                     | 36,000                | -   | Yes | Damp             | Instant or PRS Ballast |
|                                                                                            | G13       | 15    | 35900      | LED15ET8/840-V6P |       | 6          | 48       | 1750           | 4000K              | 80+ |                     | 36,000                | -   | Yes | Damp             | Instant or PRS Ballast |
|                                                                                            | G13       | 15    | 35911      | LED15ET8/850-V6P |       | 6          | 48       | 1800           | 5000K              | 80+ |                     | 36,000                | -   | Yes | Damp             | Instant or PRS Ballast |
|                                                                                            | G13       | 15    | 35913      | LED15ET8/865-V6P |       | 6          | 48       | 1800           | 6500K              | 80+ |                     | 36,000                | -   | Yes | Damp             | Instant or PRS Ballast |
| Integrated 3 ft LED Glass Tubes (operates on Instant Start or Program Start Ballast)       |           |       |            |                  |       |            |          |                |                    |     |                     |                       |     |     |                  |                        |
|                                                                                            | G13       | 11    | 35783      | LED11ET8/G/3/830 |       | 20         | 36       | 1350           | 3000K              | 80+ |                     | 50,000                | -   | Yes | Damp             | Instant or PRS Ballast |
|                                                                                            | G13       | 11    | 35784      | LED11ET8/G/3/835 |       | 20         | 36       | 1400           | 3500K              | 80+ |                     | 50,000                | -   | Yes | Damp             | Instant or PRS Ballast |
|                                                                                            | G13       | 11    | 35788      | LED11ET8/G/3/840 |       | 20         | 36       | 1400           | 4000K              | 80+ |                     | 50,000                | -   | Yes | Damp             | Instant or PRS Ballast |
|                                                                                            | G13       | 11    | 35789      | LED11ET8/G/3/850 |       | 20         | 36       | 1500           | 5000K              | 80+ |                     | 50,000                | -   | Yes | Damp             | Instant or PRS Ballast |
| Integrated 2 ft LED Glass Tubes (operates on Instant Start or Program Start Ballast)       |           |       |            |                  |       |            |          |                |                    |     |                     |                       |     |     |                  |                        |
|                                                                                            | G13       | 8     | 35775      | LED8ET8/G/2/830  |       | 20         | 24       | 1100           | 3000K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                            | G13       | 8     | 35776      | LED8ET8/G/2/835  |       | 20         | 24       | 1100           | 3500K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                            | G13       | 8     | 35778      | LED8ET8/G/2/840  |       | 20         | 24       | 1100           | 4000K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |
|                                                                                            | G13       | 8     | 35779      | LED8ET8/G/2/850  |       | 20         | 24       | 1100           | 5000K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Instant or PRS Ballast |

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

\*\* Minimum order quantity = 6

# UL 1993 Environmental Requirements for LED LAMPS  
Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.  
Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.  
Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.  
Notes: 1) Product descriptions ending in "7/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at  
[GELighting.com/ThinkLED](http://GELighting.com/ThinkLED)

LED replacement tubes
Remote Plastic Tubes - Type C

| Type                                                      | Base Type | Watts | Order Code | Description   | Volts | Case Qty** | MOL (In) | Lumens Initial | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | DLC | UL  | #Location Rating | Additional Information |
|-----------------------------------------------------------|-----------|-------|------------|---------------|-------|------------|----------|----------------|--------------------|-----|---------------------|-----------------------|-----|-----|------------------|------------------------|
| Remote Plastic 4 ft LED Tubes (Operates on Remote Driver) |           |       |            |               |       |            |          |                |                    |     |                     |                       |     |     |                  |                        |
| T8                                                        | G13       | 18    | 94381      | LED21T8/4/835 |       | 10         | 48       | 2400           | 3500K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Requires Driver        |
|                                                           | G13       | 18    | 94382      | LED21T8/4/840 |       | 10         | 48       | 2500           | 4000K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Requires Driver        |
|                                                           | G13       | 18    | 94383      | LED21T8/4/850 |       | 10         | 48       | 2500           | 5000K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Requires Driver        |
|                                                           | G13       | 18    | 26059      | LED21T8/4/865 |       | 10         | 48       | 2400           | 6500K              | 80+ |                     | 50,000                | -   | Yes | Damp             | Requires Driver        |
|                                                           | G13       | 13    | 38954      | LED15T8/4/830 |       | 10         | 48       | 1700           | 3000K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Requires Driver        |
|                                                           | G13       | 13    | 38957      | LED15T8/4/835 |       | 10         | 48       | 1800           | 3500K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Requires Driver        |
|                                                           | G13       | 13    | 38958      | LED15T8/4/840 |       | 10         | 48       | 1800           | 4000K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Requires Driver        |
|                                                           | G13       | 13    | 38962      | LED15T8/4/850 |       | 10         | 48       | 1800           | 5000K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Requires Driver        |
|                                                           | G13       | 13    | 38964      | LED15T8/4/865 |       | 10         | 48       | 1800           | 6500K              | 80+ |                     | 50,000                | -   | Yes | Damp             | Requires Driver        |
| Remote Plastic 3 ft LED Tubes (Operates on Remote Driver) |           |       |            |               |       |            |          |                |                    |     |                     |                       |     |     |                  |                        |
|                                                           | G13       | 16    | 82343      | LED18T8/3/835 |       | 10         | 36       | 1800           | 3500K              | 80+ |                     | 50,000                | -   | Yes | Damp             | Requires Driver        |
|                                                           | G13       | 16    | 82345      | LED18T8/3/840 |       | 10         | 36       | 1800           | 4000K              | 80+ |                     | 50,000                | -   | Yes | Damp             | Requires Driver        |
|                                                           | G13       | 16    | 82346      | LED18T8/3/850 |       | 10         | 36       | 1800           | 5000K              | 80+ |                     | 50,000                | -   | Yes | Damp             | Requires Driver        |
| Remote Plastic 2 ft LED Tubes (Operates on Remote Driver) |           |       |            |               |       |            |          |                |                    |     |                     |                       |     |     |                  |                        |
|                                                           | G13       | 8     | 65706      | LED9T8/2/835  |       | 20         | 24       | 1000           | 3500K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Requires Driver        |
|                                                           | G13       | 8     | 65707      | LED9T8/2/840  |       | 20         | 24       | 1100           | 4000K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Requires Driver        |
|                                                           | G13       | 8     | 65711      | LED9T8/2/850  |       | 20         | 24       | 1100           | 5000K              | 80+ |                     | 50,000                | Yes | Yes | Damp             | Requires Driver        |
|                                                           | G13       | 8     | 92997      | LED9T8/2/865  |       | 20         | 24       | 1000           | 6500K              | 80+ |                     | 50,000                | -   | Yes | Damp             | Requires Driver        |
| Remote Plastic LED U Tubes (Operates on Remote Driver)    |           |       |            |               |       |            |          |                |                    |     |                     |                       |     |     |                  |                        |
|                                                           | G13       | 12    | 28084      | LED14T8/U/835 |       | 15         | 22.5     | 1700           | 3500K              | 80+ |                     | 50,000                | -   | Yes | Damp             | Requires Driver        |
|                                                           | G13       | 12    | 28164      | LED14T8/U/840 |       | 15         | 22.5     | 1700           | 4000K              | 80+ |                     | 50,000                | -   | Yes | Damp             | Requires Driver        |

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

\*\* Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a "★" are not ENERGY STAR® certified.

# UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at [GELighting.com/ThinkLED](http://GELighting.com/ThinkLED)

LED replacement lamps

Remote Glass Tubes - Type C

| Type                                                      | Base Type | Watts | Order Code | Description      | Volts | Case Qty** | MOL (In) | Lumens Initial | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | DLC | UL  | #Location Rating | Additional Information             |
|-----------------------------------------------------------|-----------|-------|------------|------------------|-------|------------|----------|----------------|--------------------|-----|---------------------|-----------------------|-----|-----|------------------|------------------------------------|
| Remote 4ft LED Glass Tubes (Operates on Remote Driver)    |           |       |            |                  |       |            |          |                |                    |     |                     |                       |     |     |                  |                                    |
| T8                                                        | G13       | 18    | 62428      | LED21T8/G/4/835  | 10    | 48         | 2400     | 3500K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 18    | 62485      | LED21T8/G/4/840  | 10    | 48         | 2500     | 4000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 18    | 62487      | LED21T8/G/4/850  | 10    | 48         | 2500     | 5000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 18    | 62406      | LED21T8/G4/835HL | 10    | 48         | 2750     | 3500K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 18    | 62407      | LED21T8/G4/840HL | 10    | 48         | 2800     | 4000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 18    | 62408      | LED21T8/G4/850HL | 10    | 48         | 2800     | 5000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 18    | 91475      | LED21T8/G4/830US | 10    | 48         | 2600     | 3000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Requires Driver - Assembled in USA |
|                                                           | G13       | 18    | 91496      | LED21T8/G4/835US | 10    | 48         | 2600     | 3500K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Requires Driver - Assembled in USA |
|                                                           | G13       | 18    | 91497      | LED21T8/G4/840US | 10    | 48         | 2600     | 4000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Requires Driver - Assembled in USA |
|                                                           | G13       | 18    | 91498      | LED21T8/G4/850US | 10    | 48         | 2600     | 5000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Requires Driver - Assembled in USA |
|                                                           | G13       | 13    | 38944      | LED15T8/G/4/830  | 10    | 48         | 1700     | 3000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 13    | 38945      | LED15T8/G/4/835  | 10    | 48         | 1750     | 3500K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 13    | 38950      | LED15T8/G/4/840  | 10    | 48         | 1800     | 4000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 13    | 38951      | LED15T8/G/4/850  | 10    | 48         | 1800     | 5000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 13    | 38952      | LED15T8/G/4/865  | 10    | 48         | 1800     | 6500K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 10    | 76194      | LED12T8/G/4/830  | 10    | 48         | 1550     | 3000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 10    | 76264      | LED12T8/G/4/835  | 10    | 48         | 1600     | 3500K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 10    | 76265      | LED12T8/G/4/840  | 10    | 48         | 1650     | 4000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 10    | 76271      | LED12T8/G/4/850  | 10    | 48         | 1650     | 5000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 10    | 76278      | LED12T8/G/4/865  | 10    | 48         | 1650     | 6500K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver                    |
| Remote 3ft LED Glass Tubes (Operates on Remote Driver)    |           |       |            |                  |       |            |          |                |                    |     |                     |                       |     |     |                  |                                    |
|                                                           | G13       | 16    | 38257      | LED18T8/G/3/830  | 10    | 36         | 1800     | 3000K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 16    | 38258      | LED18T8/G/3/835  | 10    | 36         | 1800     | 3500K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 16    | 38260      | LED18T8/G/3/840  | 10    | 36         | 1900     | 4000K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 16    | 38261      | LED18T8/G/3/850  | 10    | 36         | 1900     | 5000K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver                    |
| Remote 2ft LED Glass Tubes (Operates on Remote Driver)    |           |       |            |                  |       |            |          |                |                    |     |                     |                       |     |     |                  |                                    |
|                                                           | G13       | 8     | 38933      | LED9T8/G/2/830   | 20    | 24         | 1000     | 3000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 8     | 38935      | LED9T8/G/2/835   | 20    | 24         | 1000     | 3500K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 8     | 38936      | LED9T8/G/2/840   | 20    | 24         | 1100     | 4000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 8     | 38939      | LED9T8/G/2/850   | 20    | 24         | 1100     | 5000K          | 80+                |     |                     | 50,000                | Yes | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 8     | 38943      | LED9T8/G/2/865   | 20    | 24         | 1000     | 6500K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver                    |
| Remote 8ft LED Glass Tubes (Operates on Remote Driver)    |           |       |            |                  |       |            |          |                |                    |     |                     |                       |     |     |                  |                                    |
|                                                           | Fa8       | 30    | 62326      | LED36T8/G/8/830  | 20    | 96         | 4200     | 3000K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver - Assembled in USA |
|                                                           | Fa8       | 30    | 62327      | LED36T8/G/8/835  | 20    | 96         | 4400     | 3500K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver - Assembled in USA |
|                                                           | Fa8       | 30    | 62329      | LED36T8/G/8/840  | 20    | 96         | 4400     | 4000K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver - Assembled in USA |
|                                                           | Fa8       | 30    | 62349      | LED36T8/G/8/850  | 20    | 96         | 4400     | 5000K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver - Assembled in USA |
| Remote Glass U6 Tubes (Operates on Remote Driver)         |           |       |            |                  |       |            |          |                |                    |     |                     |                       |     |     |                  |                                    |
|                                                           | G13       | 13    | 43131      | LED15T8/G/U6/830 | 12    | 22.5       | 1700     | 3000K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 13    | 43135      | LED15T8/G/U6/835 | 12    | 22.5       | 1800     | 3500K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 13    | 43143      | LED15T8/G/U6/840 | 12    | 22.5       | 1800     | 4000K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver                    |
|                                                           | G13       | 13    | 43145      | LED15T8/G/U6/850 | 12    | 22.5       | 1800     | 5000K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver                    |
| Remote 2ft LED Glass T5 Tubes (Operates on Remote Driver) |           |       |            |                  |       |            |          |                |                    |     |                     |                       |     |     |                  |                                    |
|                                                           | G5        | 13    | 76150      | LED15T5/G/2/830  | 20    | 24         | 1800     | 3000K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver                    |
|                                                           | G5        | 13    | 76164      | LED15T5/G/2/835  | 20    | 24         | 1850     | 3500K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver                    |
|                                                           | G5        | 13    | 76129      | LED15T5/G/2/840  | 20    | 24         | 1900     | 4000K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver                    |
|                                                           | G5        | 13    | 76167      | LED15T5/G/2/850  | 20    | 24         | 1900     | 5000K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver                    |
|                                                           | G5        | 13    | 76192      | LED15T5/G/2/865  | 20    | 24         | 1900     | 6500K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver                    |
| Remote 4ft LED Glass T5 Tube (Operates on Remote Driver)  |           |       |            |                  |       |            |          |                |                    |     |                     |                       |     |     |                  |                                    |
|                                                           | G5        | 31    | 91973      | LED36T5/G/4/830  | 20    | 46         | 4100     | 3000K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver                    |
|                                                           | G5        | 31    | 91976      | LED36T5/G/4/835  | 20    | 46         | 4200     | 3500K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver                    |
|                                                           | G5        | 31    | 91977      | LED36T5/G/4/840  | 20    | 46         | 4400     | 4000K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver                    |
|                                                           | G5        | 31    | 91997      | LED36T5/G/4/850  | 20    | 46         | 4500     | 5000K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver                    |
|                                                           | G5        | 31    | 92006      | LED36T5/G/4/865  | 20    | 46         | 4500     | 6500K          | 80+                |     |                     | 50,000                | -   | Yes | Damp             | Requires Driver                    |

Updated / New Product



LED replacement tubes

Remote Drivers

| Type                           | Base Type | Watts | Order Code       | Description | Volts | Case Qty** | Output Current (A) | Frequency | Eff | Output | Output Voltage | Temp (Min) | Temp (Max) | Dimmable                     | Additional Information |
|--------------------------------|-----------|-------|------------------|-------------|-------|------------|--------------------|-----------|-----|--------|----------------|------------|------------|------------------------------|------------------------|
| Lightech Drivers - Non-Dimming |           |       |                  |             |       |            |                    |           |     |        |                |            |            |                              |                        |
|                                | 18        | 93100 | LED9T8/DR/UN/2L  | 120-277V    | 10    | 0.27x2     | 50/60 Hz           | >.9       | DC  | 26-34V | -4 F           | 113 F      | -          | Maximum 2 Tubes (non potted) |                        |
|                                | 24        | 76289 | LED12T8/DR/2L    | 120-277V    | 10    | 0.21x2     | 50/60 Hz           | >.9       | DC  | 26-34V | -4 F           | 113 F      | -          | Maximum 2 Tubes              |                        |
|                                | 30        | 38970 | LED15T8/DR/UN/2L | 120-277V    | 10    | 0.44x2     | 50/60 Hz           | >.9       | DC  | 26-34V | -4 F           | 113 F      | -          | Maximum 2 Tubes (non potted) |                        |
|                                | 36        | 82347 | LED18T8/DR/UN/2L | 120-277V    | 10    | 0.53x2     | 50/60 Hz           | >.9       | DC  | 26-34V | -4 F           | 113 F      | -          | Maximum 2 Tubes (non potted) |                        |
|                                | 21        | 94384 | LED21T8/DR/1L    | 120-277V    | 10    | 0.62       | 50/60 Hz           | >.9       | DC  | 26-34V | -4 F           | 113 F      | -          | Maximum 1 Tube               |                        |
|                                | 42        | 94385 | LED21T8/DR/2L    | 120-277V    | 10    | 0.62x2     | 50/60 Hz           | >.9       | DC  | 26-34V | -4 F           | 113 F      | -          | Maximum 2 Tubes              |                        |
| Lightech Drivers - Dimming     |           |       |                  |             |       |            |                    |           |     |        |                |            |            |                              |                        |
|                                | 24        | 76290 | LED12T8/DR/D2L   | 120-277V    | 10    | 0.21x2     | 50/60 Hz           | >.9       | DC  | 26-34V | -4 F           | 113 F      | Yes        | Maximum 2 Tubes              |                        |
|                                | 48        | 76318 | LED12T8/DR/D4L   | 120-277V    | 10    | 0.21x4     | 50/60 Hz           | >.9       | DC  | 26-34V | -4 F           | 113 F      | Yes        | Maximum 4 Tubes              |                        |
|                                | 42        | 28174 | LED14/DR/D3L     | 120-277V    | 10    | 0.43x3     | 50/60 Hz           | >.9       | DC  | 26-34V | -4 F           | 113 F      | Yes        | Maximum 3 Tubes              |                        |
|                                | 30        | 38974 | LED15T8/DR/D2L   | 120-277V    | 10    | 0.44x2     | 50/60 Hz           | >.9       | DC  | 26-34V | -4 F           | 113 F      | Yes        | Maximum 2 Tubes              |                        |
|                                | 60        | 38975 | LED15T8/DR/D4L   | 120-277V    | 10    | 0.44x4     | 50/60 Hz           | >.9       | DC  | 26-34V | -4 F           | 113 F      | Yes        | Maximum 4 Tubes              |                        |
|                                | 36        | 88141 | LED18T8/DR/D2L   | 120-277V    | 10    | 0.53x2     | 50/60 Hz           | >.9       | DC  | 26-34V | -4 F           | 113 F      | Yes        | Maximum 2 Tubes              |                        |
|                                | 72        | 88139 | LED18T8/DR/D4L   | 120-277V    | 10    | 0.53x4     | 50/60 Hz           | >.9       | DC  | 26-34V | -4 F           | 113 F      | Yes        | Maximum 4 Tubes              |                        |
|                                | 42        | 60041 | LED21T8/DR/D2L   | 120-277V    | 10    | 0.62x2     | 50/60 Hz           | >.9       | DC  | 26-34V | -4 F           | 113 F      | Yes        | Maximum 2 Tubes              |                        |
|                                | 84        | 62030 | LED21T8/DR/D4L   | 120-277V    | 10    | 0.62x4     | 50/60 Hz           | >.9       | DC  | 26-34V | -4 F           | 113 F      | Yes        | Maximum 4 Tubes              |                        |
|                                | 45        | 34016 | LED21T8/DR/VLC2L | 120-277V    | 10    | 0.62x2     | 50/60 Hz           | >.9       | DC  | 26-34V | -4 F           | 113 F      | Yes        | Maximum 2 Tubes              |                        |
|                                | 72        | 63126 | LED36T8/DR/D2L   | 120-277V    | 10    | 1.06x2     | 50/60 Hz           | >.9       | DC  | 26-34V | -4 F           | 113 F      | Yes        | Maximum 2 Tubes              |                        |
|                                | 144       | 92013 | LED36T8/DR/D4L   | 120-277V    | 10    | 1.06x4     | 50/60 Hz           | >.9       | DC  | 26-34V | -4 F           | 113F       | Yes        | Maximum 4 Tube               |                        |

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

\*\* Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

# UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in “/TP” indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at  
[GELighting.com/ThinkLED](https://www.gelighting.com/ThinkLED)

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

\*\* Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

# UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "TTP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at  
[GELighting.com/ThinkLED](http://GELighting.com/ThinkLED)

# Awaken like never before the moment you turn on GE's LED replacement lamp.

Light influences people's emotions, how they view their space and their world, and how they start and end their day. GE understands this and wants to help transform your stores, buildings or facilities, while ensuring your upfront investment is paid back as quickly as possible.

If you're inspired to enhance your space — with substantial savings — call your GE Lighting representative.

To experience what we've done for our existing customers, see case studies, videos and image galleries at [gelighting.com/ThinkLED](http://gelighting.com/ThinkLED)



Product is compliant with material restriction requirements of RoHS

ENERGY STAR® is a registered U.S. mark



[www.gelighting.com](http://www.gelighting.com)

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2016 GE.

78945 (Rev 02/22/2017)