

simplicity



Application Illustration only, subject lamps not used in photo.

Plug into a new kind of energy savings.

LED replacement for CFL plug-in downlights

GE's LED plug-in lamps allow you to replace inefficient CFL 4 pin G24q/GX24 without tools or costly upgrades. Simply plug the replacement lamp into the existing ballast.

LOW-COST OPERATION

- Uses 50% less energy than CFL
- For example, using only 12 watts of energy, save over \$71 in energy costs over the rated life of a lamp versus a standard 26-watt CFL lamp based on \$0.11 per kWh
- Energy efficiency and long life mean fewer lamp replacements versus CFL light sources
- Advanced optics eliminate wasted light to deliver a more targeted beam with fewer lumens (950 vs. 1800)

COLOR RENDERING

- Available with a CRI of 80

COLOR TEMPERATURE

- Available in 2700, 3000, 3500 and 4000K

LONG LIFE

- Lasts 2.5X longer than CFL
- Up to 50,000 hours rated life (L70)

ENVIRONMENTALLY CONSCIOUS

- These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS

GE QUALITY AND RELIABILITY

- 5-year limited warranty

To learn more about saving money and energy, go to: gelighting.com/ThinkLED

When you Think LED lighting, Think GE.



ecomaginationSM



imagination at work

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

LED replacement for CFL Plug-in lamps

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Equivalent	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information	
Vertical																		
	G24q/GX24	12	96689	LED12G24q-V/835	6	5.3	1000	3500	80	26	50,000	-	-	Indoor	White			
		12	96771	LED12G24q-V/840	6	5.3	1000	4000	80	26	50,000	-	-	Indoor	White			
		12	96775	LED12G24q-V/830	6	5.3	950	3000	80	26	50,000	-	-	Indoor	White			
		12	96801	LED12G24q-V/827	6	5.3	950	2700	80	26	50,000	-	-	Indoor	White			
Horizontal																		
	G24q/GX24	12	96761	LED12G24q-H/835	6	5.2	1000	3500	80	26	50,000	-	-	Indoor	White			
		12	96769	LED12G24q-H/840	6	5.2	1000	4000	80	26	50,000	-	-	Indoor	White			
		12	96798	LED12G24q-H/830	6	5.2	950	3000	80	26	50,000	-	-	Indoor	White			
		12	96799	LED12G24q-H/827	6	5.2	950	2700	80	26	50,000	-	-	Indoor	White			

Get more information at
GELighting.com/ThinkLED

Check compatibility at
GELighting.com/LED4pin-compatibility

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: Certified as meeting ENERGY STAR® guidelines.


UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

^ Incandescent or Halogen wattage equivalencies based on ENERGY STAR® guidelines using lumens or CBCP according to lamp type



ecomaginationSM

Product is compliant with material restriction requirements of RoHS

ENERGY STAR® and the ENERGY STAR® logo are registered U.S. marks



www.gelighting.com

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2015 GE.

LEDL007 (Rev 6/12/15)