

spotlight



The energy-efficient radiance of GE's LED PAR30 short and long neck lamps is not just something you see, it's something you feel.

LED Commercial PAR30 short and long neck lamps

For efficient, long-lasting options for traditional downlight applications, GE's dimmable 10 and 12-watt LED PAR30 lamps are the perfect solution.

LOW-COST OPERATION:

- For example, using only 12 watts of energy, save over \$201 in energy costs over the rated life of a lamp versus a standard 85-watt halogen lamp based on \$0.11 per kWh
- Energy efficiency and long life mean fewer lamp replacements versus standard incandescent and halogen light sources

EXCELLENT COLOR RENDERING

- Available with a CRI of 80 - 85

COLOR TEMPERATURE

- Halogen-like color
- Available in 2700K, 3000, 3500, 4000 and 5000K

LONG LIFE

- Up to 50,000 hours rated life (L70)

DIMMABLE

- Dims from 100% to 10%

BEAM PATTERNS

- Available in 20° and 35° beam patterns

ENVIRONMENTALLY CONSCIOUS

- These lamps are energy efficient and contain no lead or mercury

GE QUALITY AND RELIABILITY

- 3-year limited warranty

To learn more about saving money and energy, go to: gelighting.com/ThinkLED

When you Think LED lighting, Think GE.

ecomaginationSM





imagination at work

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

LED PAR30 short and long neck lamps

Directional Lamps (PAR)

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty*	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Equivalent	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information			
Compact PAR30																				
	PAR30	MED	10	61922	LED10DP30S830/20	120	6	3.75	500	3720	3000	80	60W	50,000	Yes	★	Damp	Accent, 20° beam, Silver		
				61923	LED10DP30S827/20	120	6	3.75	450	3450	2700	80	55W	50,000	Yes	★	Damp	Accent, 20° beam, Silver		
				64326	LED10DP30W827/20	120	6	3.75	450	3450	2700	80	55W	50,000	Yes	★	Damp	Accent, 20° beam, White		
	12	63026	LED10DP3/FL/TP	120	3	3.75	450	1240	2700	80	55W	25,000	Yes	★	Damp	Accent, 35° beam, Silver				
		65137	LED12DP30S827/20	120	6	3.75	740	4400	2700	83	75W	25,000	Yes	★	Damp	Accent, 20° beam, Silver				
		65133	LED12DP30S/FL/TP	120	3	3.75	740	2000	2700	83	80W	25,000	Yes	★	Damp	Accent, 35° beam, Silver				
		67256	LED12DP30S840/20	120	6	3.75	840	5300	4000	85	90W	25,000	Yes	★	Damp	Accent, 20° beam, Silver				
		67257	LED12DP30S840/35	120	6	3.75	840	2200	4000	85	90W	25,000	Yes	★	Damp	Accent, 35° beam, Silver				
		94215	LED12DP302W83020	120	6	3.66	950	7300	3000	84	85W	25,000	Yes	★	Damp	Accent, 20° beam, White				
		94216	LED12DP302W83035	120	6	3.66	950	2700	3000	84	85W	25,000	Yes	★	Damp	Accent, 35° beam, White				
		94219	LED12DP302W82720	120	6	3.66	850	6600	2700	84	85W	25,000	Yes	★	Damp	Accent, 20° beam, White				
		94220	LED12DP302W82735	120	6	3.66	850	2300	2700	84	85W	25,000	Yes	★	Damp	Accent, 35° beam, White				
		89988	LED12DP302/FL/TP	120	3	3.66	850	2300	2700	84	75W	25,000	Yes	★	Damp	Accent, 35° beam, White				
		Compact PAR30 Long Neck																		
			PAR30L	MED	10	61924	LED10DP3LS830/20	120	6	4.75	500	3720	3000	80	60W	50,000	Yes	★	Damp	Accent, 20° beam, Silver
61925	LED10DP3LS827/20					120	6	4.75	450	3450	2700	80	55W	50,000	Yes	★	Damp	Accent, 20° beam, Silver		
68014	LED10DP3LS827/35					120	6	4.75	450	1240	2700	80	55W	25,000	Yes	★	Damp	Accent, 35° beam, Silver		
12	63027		LED10DP3L/FL/TP	120	3	4.75	450	1240	2700	80	55W	25,000	Yes	★	Damp	Accent, 35° beam, Silver				
	65141		LED12DP3LS827/20	120	6	4.75	740	4400	2700	83	75W	25,000	Yes	★	Damp	Accent, 20° beam, Silver				
	65134		LED12DP3LS/FL/TP	120	3	4.75	740	2000	2700	83	80W	25,000	Yes	★	Damp	Accent, 35° beam, Silver				
	94212		LED12DP3L2W83020	120	6	4.61	950	7300	3000	84	85W	25,000	Yes	★	Damp	Accent, 20° beam, White				
	94214		LED12DP3L2W83035	120	6	4.61	950	2700	3000	84	85W	25,000	Yes	★	Damp	Accent, 35° beam, White				
	94218		LED12DP3L2W82735	120	6	4.61	850	2300	2700	84	85W	25,000	Yes	★	Damp	Accent, 35° beam, White				
	11306		LED12DP3L2W83535	120	6	4.61	950	2700	3500	84	85W	25,000	Yes	★	Damp	Accent, 35° beam, White				
	89989		LED12DP3L2/FL/TP	120	3	4.61	850	2300	2700	84	75W	25,000	Yes	★	Damp	Accent, 35° beam, White				
	22233		LED12DP3L2FL5KTP	120	3	4.61	1050	3000	5000	84	75W	25,000	Yes	★	Damp	Accent, 35° beam, White				

Get more information at
GELighting.com/ThinkLED

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

★ ENERGY STAR® status: Certified as meeting ENERGY STAR® guidelines.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

^ Incandescent or Halogen wattage equivalencies based on ENERGY STAR® guidelines using lumens or CBCP according to lamp type



ecomaginationSM

Product is compliant with material restriction requirements of RoHS

ENERGY STAR® and the ENERGY STAR® logo are registered U.S. marks



www.gelighting.com

GE and the GE Monogram are trademarks of the General Electric Company. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
© 2014 GE Lighting.

76221 (Rev 07/28/14)