GE Lighting

upgrade



Application illustration only, subject lamps not used in photo.

LED High Lumen Biax® Plug-In

GE's LED high lumen Biax[®] plug-in lamp provides an easy solution to leverage the low energy and long life of LED. Simply plug in the LED lamp into the existing fluorescent fixture, no tools, wiring, or costly upgrades required.

LOW COST OPERATION

- Uses 30% less energy
- For example, using only 17 watts of energy, save over \$44 in energy costs over the rated life of a lamp vs. a standard 25-watt CFL plug-in based on \$0.11 per kWh
- Advanced optics eliminate wasted light to deliver a more targeted beam with fewer lumens (2150 vs. 2600)

COLOR TEMPERATURE

• Available in 3000K, 3500K, 4000K and 5000K

LONG LIFE

- Lasts 2.5X longer than CFL plug-in
- 50,000 hours rated life (L70)

GE QUALITY AND RELIABILITY

• 3 year limited waranty

ENVIRONMENTALLY CONSCIOUS

• These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS

To learn more about saving money and energy, go to: **gelighting.com/ThinkLED**

When you Think LED lighting, Think GE.

ecomagination[™]



Product Specifications

LED High Lumen Biax[®] plug-in lamp

Bulb	Base		Order			Case		Lumens		Initial Color		Wattage	*Rated Life		#Locatior	n Additional
Shape	Туре	Watts	Code	Description	Volts	Qty"	MOL (In)	Initial	CBCP	Temp	CRI	Equiv.	L70 (Hrs) Di	mmable	Rating	Information
	2G11	17	39073	LED172G11/830/10	##	10	21.85	2150		3000	80		50000	-	Damp	Indoor, White, instant/programmed start ballast
		17	39074	LED172G11/835/10	##	10	21.85	2150		3500	80		50000	-	Damp	Indoor, White, instant/programmed start ballast
		17	39075	LED172G11/840/10	##	10	21.85	2200		4000	80		50000	-	Damp	Indoor, White, instant/programmed start ballast
		17	39076	LED172G11/850/10	##	10	21.85	2200		5000	80		50000	-	Damp	MTO, 1000 minimum quantity, 12 week lead time

Check compatibility at GELighting.com/LED2G11-Compatibility

Get more information at **GELighting.com/ThinkLED**

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70) ** Minimum order quantity = 10

UL 1993 Environmental Requirements for LED LAMPS
Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.
Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.
Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Check ballast compatibility at: GELighting.com/LED2G11-Compatibility



Product is compliant with material restriction requirements of RoHS

ecomagination™



www.gelighting.com

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2016 GE.

LEDL031 (Rev 2/23/16)